





This is to certify that: **RPB Safety LLC**

2807 Samoset Rd

Royal Oak Michigan 48073 **USA**

Holds Certificate Number: CE 718714

In respect of:

PX5 AIR PAPR System incorporating the following headtop systems: T-Link, Z-Link, Z4 & T200.

to EN 12941:1998+A2:2008 - Respiratory protective devices - Powered filtering devices incorporating a helmet or hood.

on the basis that BSI carried out the relevant Type Examination procedures under the requirements with the Regulation (EU) 2016/425 of the European Parliament and Council relating to Personal Protective Equipment Regulation (PPE) Annex V (Module B) and meets the relevant health and safety requirements specified in Annex II

For and on behalf of BSI, a Notified Body for the above Regulation (Notified Body Number 2797):

Drs. Dave Hagenaars, Managing Director

First Issued: 2020-06-02 Latest Issue: 2021-06-18 Effective Date: 2021-06-18 Expiry Date: 2025-06-02

Page: 1 of 7



...making excellence a habit.™

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request. To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated online.

No. CE 718714

Product Specification

Range: PX5 Advanced PAPR System incorporating the following Head-tops:

Head-tops: T-LINK, Z-LINK, Z4 & T200.

Technical EN 12941:1998+A2:2008 – Respiratory protective devices - Powered filtering devices

Specification: incorporating a helmet or hood

Product Description: The RPB® PX5® is approved as a Powered Air Purifying Respirator Fan Unit to EN

12941:1998 + A1: 2003 + A2: 2008, designed to be used in conjunction with the approved RPB® head-tops for different applications where there is a need for protection from airborne contaminants such as welding, grinding, painting, and other construction and industrial applications, depending on the selected head-top. For applications such as welding or grinding that produce sparks or high heat, a FR (Fire Retardant) specific model is available, with a FR belt and spark arrester to prevent

sparks from entering the PAPR and igniting the filter material.

For applications that need cleaning and disinfecting, a DC (Easy Clean) specific model

is available, with a DC Belt which has a coating for easily wiping and washing.

Model numbers: 03-801, 03-801-FR, 03-801-DC (HEPA Filter Configurations)

03-802, 03-802-FR, 03-802-DC (Combination Filter Configurations)

			Filters					Hose	Belt/Backpack				Battery			
Headtops	Standard	PX5 Air Protection	03-892-P P R SL (HEPA)	03-893-A2 - A2P R SL (Combined)	03-895-ABEKABEK1P R SL (Combined)	03-894-ABEABE1P R SL (Combined)	Number of Filters Used	MMDF	04-831	07-765	07-765-FR	DQ-592-L0	03-822-FR	03-825-DC	03-855	03-856
Z4	EN12941	TH2	Yes	Yes	Yes	Yes	1	180 I/min	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Z-Link	EN12941	TH2/3	Yes	Yes	Yes	Yes	1	180 I/min	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
T-Link	EN12941	TH3	Yes	Yes	Yes	Yes	1	180 I/min	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
T200	EN12941	TH3	Yes	Yes	Yes	Yes	1	180 I/min	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Page: 2 of 7

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated online.

No. CE 718714

Associated Head-Tops:

Product name: T-LINK PAPR Respiratory Helmet with Full Face Visor.

Product variants: Standard Bib - TH3

Extra Long Bib - TH3

Product type: T-Link Respiratory Helmet with Full Face Visor & optional Ear-muffs.

The T-Link Respiratory Helmet with Full Face Visor is designed to only be used as part of RPB PX4 and PX5 AIR Respiratory systems approved to EN 12941:1998+A2:2008. The T-Link is designed to operate with a flow rate between 180-230 litres per minute and compatible for use with PX4 and PX5 PAPR systems. Respiratory characteristics

are specified on page 2 of this certificate.

The T-Link Helmet is approved to be used in combination with the Quiet Link Earmuffs to EN 352-3:2002 Hearing protectors – Ear-muffs attached to an Industrial

Helmet.

Technical Specification: EN 12941:1998+A2:2008 – Respiratory protective devices - Powered filtering devices

incorporating a helmet or hood.

HEAD-TOP TYPE	FILTER	MMDF	MIN RUN TIME
T-LINK	HEPA	180 //min	10.00 hrs (Speed 1)
			07.00 hrs (Speed 2)
			06.00 hrs (Speed 3)
	Combined	180 l/min	05.00 hrs (Speed 1)
			04.00 hrs (Speed 2)
			04.00 hrs (Speed 3)

Technical Specification & Classifications:

EN 166:2001 Personal eye-protection (CE 698662)— Optical class 1, Impact Low and liquid splash.

Classification: 1 F 3

EN 812:2012 Industrial Bump Cap

The Respiratory Helmet meets Technical Specification to the mechanical requirements of EN 397:2012+A1:2012, 5.1.1 Shock Absorption, 5.1.2 Resistance to penetration & 5.1.3 Flame Resistance

Quiet Link Ear-Muff

EN 352-3:2002 Hearing protectors – Ear-Muff attached to an Industrial Helmet.

SNR = 33dB H = 37dB M = 30dB L = 23dB

Page: 3 of 7

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

Product name: Z-LINK PAPR Respiratory Helmet with Full Face Visor.

Product variants: Face Seal - TH2 Chin Seal - TH2

Shoulder Cape – TH3

Product type: Z-Link Respiratory Helmet with Full Face Visor & optional Ear-muffs.

The Z-Link Respiratory Helmet with Full Face Visor is designed to be used as part of RPB PX4 and PX5 AIR Respiratory systems approved to EN 12941:1998+A2:2008. The Z-Link is designed to operate with a flow rate between 180-230 litres per minute and compatible for use with PX4 and PX5 PAPR systems. Respiratory characteristics

are specified on page 2 of this certificate.

The Z-Link Helmet is approved to be used in combination with the Quiet Link Earmuffs to EN 352-3:2002 Hearing protectors – Ear-muffs attached to an Industrial

Helmet.

Technical Specification: EN 12941:1998+A2:2008 – Respiratory protective devices - Powered filtering devices

incorporating a helmet or hood.

Combined 180 l/min 05.00 hrs (Speed 1)

04.00 hrs (Speed 2)

04.00 hrs (Speed 3)

Technical Specification & Classifications:

EN 166:2001 Personal eye-protection (CE 698662) – Optical class 1, Impact for high speed particles at extreme temperature, Molten Metal Hot Solids and Liquid Splash.

Classification: 1 BT 9 3

EN 169:2002, EN 170:2002 & EN 172:1994+A2:2001 filter requirements.

Filters Type: Scale:

Clear 2-1.2 or 2C-1.2

Smoke 5-3.1

Yellow 2-1.2 or 2C-1.2

Mirror 5-3.1 IR5 4-5

The Respiratory Helmet meets Technical Specification to the mechanical requirements of EN 397:2012+A1:2012, 5.1.1 Shock Absorption, 5.1.2 Resistance to penetration & 5.1.3 Flame Resistance and very low temperature, Molten Metal Splash, Lateral Deformation and Electrical Properties (440v) only.

Classification: -30°C / 440 V a.c / LD / MM

Page: 4 of 7

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

Quite Link Ear-muff - EN 352-3:2002 Ear protection. SNR- 33dB / H- 37dB / M- 30dB / L- 23dB

Product name: Z4 PAPR Respiratory Helmet with Full Face Visor.

Product variants: Face Seal – TH2

Shoulder Cape - TH2

Product type: Z4 Welding Helmet with full face Visor. The Helmet is designed to be fitted with ADF

units approved to EN 379:2003+A1:2009 and meets the requirements of EN 175:1997. The Z4 Welding Helmet with full face visor is designed to only be used as part of RPB

PX4 and PX5 AIR Respiratory systems approved to EN 12941:1998+A2:2008.

The Z4 is designed to operate with a flow rate between 180-230 litres per minute and compatible for use with PX4 and PX5 PAPR systems. Respiratory characteristics are

specified on page 2 of this certificate.

Technical Specification: EN 12941:1998+A2:2008 – Respiratory protective devices - Powered filtering devices

incorporating a helmet or hood.

HEAD-TOP TYPE FILTER MMDF MIN RUN TIME

Z4 HEPA 180 //min 10.00 hrs (Speed 1)

07.00 hrs (Speed 2)

06.00 hrs (Speed 3)

Combined 180 l/min 05.00 hrs (Speed 1)

04.00 hrs (Speed 2)

04.00 hrs (Speed 3)

Technical Specification & Classifications:

EN 166:2001-Personal eye protection. (CE 698661) Optical class1 and Medium Impact.

Classification: 1 B

EN 175:1997 Personal eye-protection - Equipment for eye and face protection during welding and allied processes.

EN 379:2003+A1:2009 Personal eye-protection – Automatic Welding Filters

Classification: RPB 16-871 - 3/9-13 RPB 1/1/1/2/379 CE (EN 379:2003+A1:2009)

EN 812:2012 Industrial bump caps.

Page: 5 of 7

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

Product name: T200 PAPR Respiratory Helmet with Full Face Visor.

Product variants: Face Seal – TH3

Full Hood - TH3

Product type: T200 Respiratory Helmet with Full Face Visor & optional Ear-muffs.

The T200 Respiratory Helmet with Full Face Visor is designed to only be used as part of the PX5 AIR Respiratory systems approved to EN 12941:1998+A2:2008. The T200 is designed to operate with a flow rate between 180-230 litres per minute and compatible for use with PX5 PAPR systems. Respiratory characteristics are

specified on page 2 of this certificate

Technical Specification: EN 12941:1998+A2:2008 – Respiratory protective devices - Powered filtering devices

incorporating a helmet or hood.

 HEAD-TOP TYPE
 FILTER
 MMDF
 MIN RUN TIME

 T200
 HEPA
 180 //min
 10.00 hrs (Speed 1)

 07.00 hrs (Speed 2)
 06.00 hrs (Speed 3)

Combined 180 l/min 05.00 hrs (Speed 1)

04.00 hrs (Speed 2)

04.00 hrs (Speed 3)

Technical Specification & Classifications:

EN 166:2001-Personal eye protection. (CE 698661) Optical class 1, Low Impact, Liquid Splash.

Classification: 1 F 3

Page: 6 of 7

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

Certificate Administration Details

Technical File Reference: PX5 PAPR

Certificate Administration Record and BSI internal Technical File Review refere

Issue date	Comments	BSI Review Ref.
April 2020	First issue – PX5 with T-Link.	2797:20:3082038
January 2021	Update to include the Z-Link, Z4 & T200.	2797:21:3264883
June 2021	Scope update to PAPR system to add Combined filters ABEK1P R SL & ABE1P R SL. Classification upgrade to TH3 Z-Link (Shoulder Cape) Scope update to Z4 EN 379:2003+A1:2009 & EN 812:2012. Scope update to Z-Link EN 166:2001 and EN 397:2012+A1:2012. Scope update to T-Link EN 166:2001 and addition of EN 812:2012 Addition of EN 166:2001 to the TF200.	2797:21:3410625

Certificate validity

The Certificate holder is responsible for ensuring that the Notified Body is advised of changes to any aspect of the overall process utilised in the manufacture of the product, failure to do so could invalidate the Certificate in respect of product manufactured following the introduction of such changes.

Maintenance & Monitoring of manufactured PPE

The Module B certification requires the continual maintenance and monitoring of the conformity to type based on Quality Assurance of the Production Process, Annex VIII (Module D), for the product that are referenced in BSI issued Module D Certificate Number CE 705839.

Page: 7 of 7

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.