



Main

| | |
|---------------------------|---|
| Product or component type | Switch |
| Device application | Control |
| Load type | Inductive Resistive Incandescent lamp Fluorescent lamp |
| Colour tint | Dark grey |

Complementary

| | |
|------------------------------|--|
| Device presentation | Complete product |
| Rated current | 16 AX at 250 V AC 50/60 Hz |
| Switch function | 1-pole 1-way |
| Number of gangs | 3 gangs |
| Number of rocker | 3 |
| Clamping connection capacity | 3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s) |
| Connections - terminals | Brass terminal |
| Material | Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator |
| Device mounting | Surface Flush |
| Width | 86 mm |
| Height | 86 mm |
| Depth | 34.2 mm |

Environment

| | |
|---|--|
| IP degree of protection | IP20 |
| Maximum ambient air temperature for operation | 45 °C |
| Operating altitude | 2000 m |
| Relative humidity | 0...95 % |
| Environmental characteristic | UV resistant |
| Standards | BS EN 60669-1 MS IEC 60669-1 IEC 60669-1 SS 227-1 |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | 📄 REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant 📄 EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | 📄 Yes |
| China RoHS Regulation | 📄 China RoHS Declaration |