



PIG® Paint Booth Mat with Adhesive Backing

MAT32300 32" x 100', 1 roll

Protects your spray booth floors and mixing room surfaces from build up by collecting the overspray, dust and particles that cause paint defects or create a fire hazard.

- Top surface helps attract and trap dust, dirt and paint and primer overspray before it causes paint defects during a spray job; mat keeps paint booth clean, bright and running efficiently
- Protect mixing room benches, tables or other work surfaces by cutting mat to the size you need
- Self-sticking adhesive back keeps mat securely in place without shifting, sliding or causing a trip hazard
- Installs quickly, peels up for fast, easy changeouts and lasts up to 3 months depending on amount of overspray and cleaning
- Durable enough for heavy foot and vehicle traffic; padding reduces noise and makes standing and kneeling more comfortable
- Bright blue and gray color options create better color matching and help to reduce casting and eliminate shadows and reflections
- Easy to control build up! No need to scrape or use chemicals to remove overspray from your floor; you can sweep or vacuum daily to remove dried overspray, dust and debris
- Helps extend the life of paint booth filters
- Apply to clean, dry surface; scrape loose build up to ensure adherence
- Not for vertical surfaces
- Add tape over the seams to reduce fraying of the edges, prevent air particulates from being trapped under the mat and help preserve the lifecycle of the mat
- Meets NFPA33 – Static Dissipative & OSHA Standards at conditions of 50% RH or higher



Item#	Description	Dimensions	Weight
MAT32300-BL		32" W x 100' L	

MAT32300-GY

32" W x 100' L

Metric Equivalent:

Item#	Description	Dimensions	Weight
MAT32300-BL		81.3cm W x 30m L	
MAT32300-GY		81.3cm W x 30m L	

Specifications

Dimensions	32" W x 100' L
Recycled Content	25% or more Recycled Content
Backing Material	Adhesive-Backed
Brand	PIG
Category	Paint Booth Mat
Core Diameter	3"
Flammability Specifications	Flame Resistant - Will melt and self-extinguish
Fluid Absorbed	Paints; Stains; Solvents
Ideal For	Automotive Painting & Refinishing; Auto Repair; Body Shops; Car Dealerships
Incinerable	Yes
Industry	Automotive; Industrial Facilities; Manufacturing; Shops & Garages
Indoor/Outdoor	Indoor Use
Perforated	No
Storage Temp Range	Store between 32°F and 120°F
Temperature Limit	Surface temps from 55°F to 120°F Continuous, 200°F Intermittent
Traffic	Vehicle Traffic; Heavy Foot Traffic
UV Resistant	No
Walking Surface	Absorbent Top
Sold as	1 roll
# per Pallet	13
Composition	Absorbent - Polypropylene Stitching - Polyester Adhesive Backing - Proprietary Adhesive Material
UNSPSC	47131901
Pigalog® Page Number	<u>Page 233</u>

Metric Equivalent

Dimensions	81.3cm W x 30m L
------------	------------------

Technical Information

Certifications, Approvals and Ratings

NFSI Certified,ANSI B101.1- 2009

Technical Documents

[PIG Grippy® Absorbent Mat](#)

[New Pig Adhesive-Backed Mat Notice](#)

[PIG® Grippy® Absorbent Mats](#)

[29 CFR 1910.22\(a\)\(2\)](#)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com