



Main

Range	Affle Plus
Product or component type	Switch
Device application	Control switch
Load type	Heater Air conditioner
Colour tint	White

Complementary

Device mounting	Flush
Switch function	2-pole 1-way
Cable cross section	8 x 4 mm ² solid cable for AC 4 Mm ² stranded cable 2.5 Mm ² solid cable 2.5 mm ² stranded cable
Rated current	20 A at 250 V AC
Number of gangs	2 gangs
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: surround Polycarbonate: actuator PA66 GF30: tip
Connections - terminals	Screw terminal
Embedding depth	20.1 mm
Width	86 mm
Height	86 mm
Depth	33.4 mm

Environment

Maximum ambient air temperature for operation	35 °C
Relative humidity	0...95 %
Operating altitude	5000 m
Product certifications	IEC
Standards	IEC 60669-1 BS EN 60669-1 MS IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	95 g
Package 1 Height	3.3 cm
Package 1 width	8.6 cm
Package 1 Length	8.6 cm
Unit Type of Package 2	BB1

Number of Units in Package 2	8
Package 2 Weight	760 g
Package 2 Height	9.5 cm
Package 2 width	15 cm
Package 2 Length	19 cm
Unit Type of Package 3	P12
Number of Units in Package 3	1536
Package 3 Weight	145.92 kg
Package 3 Height	100 cm
Package 3 width	80 cm
Package 3 Length	120 cm