Product data sheet Characteristics

A3GT25_WE_G2

13A Twin Gang Switched Socket, White



Main

Range	Affle Plus
Product or component type	Switched socket
Device presentation	Mechanism
Outlet poles configuration	3P with shutter
Outlet standard description	With earthing contact
Outlet standard	BS 1363
Colour tint	White
Type of packing	Flow-pack
Sale per indivisible quantity	1
Number of terminals	3

Complementary

Socket number	2
Device mounting	Flush
Fixing mode	Screw
Surface finish	Glossy
Surface treatment	Untreated mechanism cover
Rated current	13 A socket-outlet
[Ue] rated operational voltage	250 V AC 50/60 Hz
Service life in cycles	15000 cycles
Electrical durability	15000 cycles
Connections - terminals	Screw terminal
Screwdriver shape	Philips No 2
Number of cables	2
Clamping connection capacity	2.54 mm² for rigid cable(s) 2.54 mm² for stranded cable(s) 2.54 mm² for flexible cable(s)
Wire stripping length	14 mm
Material	PC (polycarbonate) Brass
Height	86 mm
Width	146 mm
Depth	29.2 mm
Embedding depth	18.3 mm
Product weight	0.114 kg

Environment

-545 °C	
-545 °C	
BS 1363 MS 589	
SIRIM	
IP20	
	-545 °C BS 1363 MS 589 SIRIM

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	121 g
Package 1 Height	2.9 cm
Package 1 width	8.6 cm
Package 1 Length	14.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	7
Package 2 Weight	850 g
Package 2 Height	9.5 cm
Package 2 width	15 cm
Package 2 Length	19 cm
Unit Type of Package 3	P12
Number of Units in Package 3	1344
Package 3 Weight	171.2 kg
Package 3 Height	100 cm
Package 3 width	80 cm
Package 3 Length	120 cm