









FLT521 For Oil, Each absorbs up to 33 gal., Max Flow Rate 8 gal./Minute

Pour-through filter system uses replaceable absorbents and gravity for easy separation of oil from water.

- System separates oil from water through gravity; simply pour liquid into the filter and filtered water flows out of drain
- Replaceable Oil-Only Absorbent Pillows are easy to change and can be rotated for maximum life
- 55-gallon Drum Filter handles filtration of up to 8 gallons of liquid per minute
- Durable polyethylene drum won't rust or corrode
- Outflow pipe accepts hose connection for easy draining of filtered water



Specifications

Includes

Opcomodions	
Absorbency Range	30 - 39.9 gal.
Style	Oil, Water Separator
Dimensions	ext. dia. 24" x 39" H
Absorbency	Up to 33 gal.
Brand	PIG
Drain	.75" NPT
Color	Blue/Tan
Max Flow Rate	8 gal./Minute
Substance Filtered	Oil
Sold as	1 each
Weight	56 lbs.
# per Pallet	2
Composition	Drum: Polyethylene
	Filter Media: Cellulose & Polypropylene

6 - 28" W x 30" L x 3" H Oil-Only Pillows

1 - ext dia. 23.5" x 6" H Polyethylene Diffuser Funnel

UNSPSC	47101514
Pigalog® Page Number	Page 51
Metric Equivalent	
Absorbency	Up to 124.9 L
Weight	25.4 kg

Technical Information

Technical Documents

Instructions for PIG Oily Water Drum Filter

Absorbent W

Dimensions

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

ext. dia. 61cm x 99cm H

1 - 55-Gallon Poly Filtering Drum

1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com