



Chemical protection

ULTRANEО 339

Prolonged contact (or immersion) | continuous wear

Comfort and high-level chemical protection

SPECIFIC ADVANTAGES

Thermal protection

- Thermal insulation from the cotton-knit lining for handling hot liquids



Durability

- Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove



Productivity

- Pebbled embossing, for better grip on wet and slippery objects



Skin protection

- Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Mechanical industry
- Chemical industry

APPLICATIONS

- Surface treatment of metals (acids)
- Handling and transporting drums of chemical products
- Handling on alkylation units
- Hot, petrochemical product sampling
- Resin-working
- Site pollution control



CHEMICAL PROTECTION
TYPE A

EN388



3121X

EN ISO 374-1



TYPE A
ABCJLMNS

CAT.3



0334

EN407



X1XXXX



Chemical protection

ULTRANEО 339

Prolonged contact (or immersion) | continuous wear

LEGENDS

| EN388 | | MECHANICAL HAZARDS | |
|---------------------------------------|-----|-------------------------------------|-----------|
| | | PERFORMANCE LEVELS (X = NOT TESTED) | |
| 3 | 1 | 2 | 1 X |
| 0-4 | 0-5 | 0-4 | 0-4 A-F P |
| Impact protection (optional) | | | |
| Cut resistance according to ISO 13997 | | | |
| Puncture resistance | | | |
| Tear resistance | | | |
| Blade cut resistance | | | |
| Abrasion resistance | | | |

| EN407 | | THERMAL RISKS (HEAT AND FIRE) | |
|--|-----|-------------------------------------|-------------|
| | | PERFORMANCE LEVELS (X = NOT TESTED) | |
| X | 1 | X | X X X |
| 0-4 | 0-4 | 0-4 | 0-4 0-4 0-4 |
| Resistance to large quantities of molten metal | | | |
| Small splashes of molten metal | | | |
| Radiant heat resistant | | | |
| Convective heat resistance | | | |
| Contact heat resistance | | | |
| Limited flame spread | | | |

| EN ISO 374-1 | | CHEMICAL RISKS | |
|--------------|--|--------------------------|--|
| | | TYPE A | |
| | | A: Methanol | |
| | | B: Acetone | |
| | | C: Acetonitrile | |
| | | J: n-Heptane | |
| | | L: Sulphuric acid 96% | |
| | | M: Nitric acid 65% | |
| | | N: Acetic acid 99% | |
| | | S: Hydrofluoric acid 40% | |

PRODUCT DETAILS

| | |
|---|-----------------|
| Interior finish | Textile support |
| Exterior finish | Pebbled |
| Material | Polychloroprene |
| Cuff characteristic | Feston Cuff |
| Colour.s | Black |
| Length (cm) | 36 |
| Thickness (mm) | 1.6 |
| Size | 8 9 10 11 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 2.9E+11 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 1.2E+11 Ω |

LOGISTIC DETAILS

| | |
|-----------|------------------------------|
| Packaging | 1 pair/bag 6 pairs/carton |
|-----------|------------------------------|

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2912 updated 01-11/10/2021
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France