

PIRANHA adjustable I'yrd 2m, no connectors

LA02

Adjustable lanyard for working position and work restraint.

Features:

- · Range of lengths & connector options
- · One hand operation
- Precise adjustment
- · Protective sleeve on rope and eyes
- · User replaceable rope
- Individual ID number

Simply pull to tighten or press the recessed catch to loosen. User can always maintain a grip of the structure for support when adjusting.

Cam locks as soon as load is applied resulting in no slack in the lanyard and no unwanted movement for the user.

Sleeve protects against abrasion, sharp edges and contamination. Adhesive heat shrink prevents the ID label from being damaged or lost.

Replacement ropes available (LAR***) see table below. Can be fitted by the user in minutes and requires only a screwdriver.

Use of screwlinks (certain models) helps eliminate risk of side or cross loads, and can be a semi-permanent attachment if required.

NB: When used for positioning, use additional fall protection system.

Meets the requirements of EN795 type B.

Code	Length	Anchorage connector Harness connector	
LA02	2m	none	none
LA02H	2m	safety hook	screwlink
LA02T	2m	twistlock	triact*
LA02TH	2m	safety hook	tri-act
LA02S	2m	scaffhook	triact
LA03	3m	none	none
LA03H	3m	safety hook	screwlink
LA05	5m	none	none
LA05H	5m	safety hook	screwlink
LA10	10m	none	none
LA20	20m	none	none

^{*} complies with Siemens PPE requirements PRO-13838 Ap1



Patented GB2543699

Specifications:

NB: specifications and colour may change without notice.

Size: 2m - 20m

EN Test Mass: 125kg

Loading: 1 person

Conformity: EN358:2018

Materials: Anodised Aluminium Alloy, Polyamide, Stainless Steel

Weight (kg): 0.60

Industries: Roof safety, wind turbine climbers, telecoms and pylon climbing, fire and rescue service, USAR.

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997