

PIG™ Pipe Wrap Repair Kit for Lines & Joints Under Pressure

PTY123 Pressurized, For Up to 2" dia.

Polyurethane-infused fiberglass wrap provides fast, easy way to permanently fix broken, corroded or leaking pipes to beyond their original strength.

- Each kit contains materials for restoring one pipe or joint, even if pressurized up to 60psi
- Works on most pipes, including PVC, copper, galvanized steel, rubber, lead and iron
- Materials adhere to wet or dry surfaces to allow repairs without draining pipes
- Pressure-sensitive tape and PIG® Repair Putty apply underneath outer wrap to strengthen seal
- Nitrile gloves protect hands during repair
- Cures in approximately 30 minutes at 75°F
- Final repair is not affected by salt water
- NSF Certified for safe use on potable water lines



Specifications

Brand	PIG
Cure Time	30 Minutes at 75°F (24°C)
Pipe Pressure	Pressurized
Pipe Size	Up to 2" dia.
Temperature Limit	300°F (149°C) Continuous/500°F (260°C) Intermittent
Distributor Part Number	5939484;04088x10223
Sold as	3 per box
Weight	2.26 lbs.
# per Pallet	432
Composition	Putty - Epoxy Pressure-Sensitive Tape - Rubber Gloves - Nitrile Wrap - Polyurethane/Fiberglass
Includes	2 - 1.5" L PIG™ Multi-Purpose Epoxy Putty (PTY230) 1 - 5' L x 1" W Pressure-sensitive Tape 1 - Pair Nitrile Gloves 1 - 9' L x 3" W Polyurethane-impregnated Fiberglass Wrap
Shelf Life	730 days
UNSPSC	31201519

Metric Equivalent

Weight	1 kg
--------	------

Technical Information

Certifications, Approvals and Ratings

NSF Certified

CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Great Britain, Japan.

Technical Documents

[Instructions for Using PIG® Pipe Wrap Repair Kit on Pipes Under Pressure](#)

[PIG® Multi-Purpose Repair Putty](#)

[PIG® Wrap for Pipes](#)

**New Pig**

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com