

## **Product Specification Sheet**

## WORKSafe® FR FACE MASK RESPIRATORY PROTECTION



Reliable, reusable masks that will shield you from workplace heat hazards. This fireresistant mask defends well against heat hazards such as flash fires and sudden flames. An anti-bacterial inner layer makes it suitable for blocking microbial hazards.

## **Product Info:**

- Made of Nomex<sup>®</sup> IIIA fabric, renowned for its comfort, fire resistant and moisturewicking properties.
- Available in five colours.
- Suitable for utilities, manufacturing, oil & gas and chemical industrial work.

## Notes for use:

- Wash your mask frequently to ensure that no greases, oily soils or other flammable contaminants are present during use.
- Ensure that the FR masks are clean and in proper condition before each wearing.
- Retire any mask with visible holes, rips, and/or tears or contamination from flammable materials.
- Destroy retired masks so that they cannot be re-used.

PRODUCT CODE 400WSRNMXOR2P (Orange) 400WSRNMXNB2P (Navy blue) 400WSRNMXRB2P (Royal blue) 400WSRNMXRD2P (Red) 400WSRNMXGY2P (Grey)

Brand	WORKSafe	Model	FR Face Mask
Туре	Respiratory Protection		
Width	250mm	Height	145mm
Standards	Outer layer fabric: Tested with NFPA 2112, NFPA 70E Inner layer fabric: Tested with ASTM D6413-13b, AATCC 100		
Outer Layer Fabric	Nomex <sup>®</sup> III A (93% Nomex <sup>®</sup> , 5% Kevlar <sup>®</sup> , 2% P140 (Static dissipative fibre)		
Inner Layer Fabric	70% FR Lenzing, 20% Nomex <sup>®</sup> , 10% Lyocell <sup>®</sup>		
Ear Loops	100% Nomex®		

For more safety tips & updates, follow us on  $(\mathbf{f})$  (in) @PDS.Safety

safetysam 🕑

PDS International Pte Ltd / T: 6776 6200 / E: pds@safety.com.sg / W: safety.com.sg