



PIG® Water-Activated Flood Bag

WTR009 Ideal For Stacking, Retaining Walls,12" W x 24" L x 3.5" H When Fully Saturated,10 per bag

Super absorbent flat bags swell up on contact with water to become a solid, heavy barrier to quickly dam and divert floodwater.

- Stack 26"-long sandbag replacements to create a retaining wall in flood-prone areas when water is coming
- Lightweight, compact and easy to handle before activated, unlike standard sandbags which are heavy, messy and labor-intensive
- Stack and stagger up to three rows high; build even higher retaining walls by using a pyramid layout
- NOTE: Not for use with salt water

Specifications

Metric Equivalent

Dimensions

Dimensions	15" W x 26" L x .25" H
Brand	PIG
Capacity	4 gal. per Bag
Dimensions When Fully Saturated	12" W x 24" L x 3.5" H When Fully Saturated
Height When Fully Saturated	3.5" When Fully Saturated
Ideal For	Stacking, Retaining Walls
Color	Black
Install/Deploy Type	Temporary/Removable Barrier
Temperature Limit	Works from 32°F to 180°F
Traffic	Non-Weight Bearing
Weight When Fully Saturated	32 lbs. each When Fully Saturated
Sold as	10 per bag
Weight	4.7 lbs.
# per Pallet	100
Composition	Skin - Polypropylene Filler - Super Absorbent Polymer (SAP)
UNSPSC	24101907
Pigalog® Page Number	Page 163

38.1cm W x 66cm L x 6.4mm H

Weight 2.1 kg

Technical Information

Technical Documents

FAQ for PIG Water-Activated Flood Bags & Barriers

Instructions for PIG Water-Activated Flood Bags & Barriers

PIG® Water Activated Flood Barriers



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com