

Safety lanyards

AZ 002
galvanized steel
opening: 18 mm
weight: 220 g



AZ 003
aluminium
opening: 20 mm
weight: 160 g



AZ 004
aluminium
opening: 22 mm
weight: 180 g
twist lock



AZ 040
aluminium
opening: 23 mm
weight: 80 g



AZ 041T
aluminium
opening: 23 mm
weight: 100 g
twist lock



AZ 020
galvanized steel
opening: 23 mm
weight: 230 g



AZ 021T
galvanized steel
opening: 23 mm
weight: 250 g
twist lock



AZ 022
galvanized steel
opening: 50 mm
weight: 500 g



AZ 023
aluminium
opening: 60 mm
weight: 480 g



AZ 024
aluminium
opening: 100 mm
weight: 920 g



AZ 025
galvanized steel
opening: 80 mm
weight: 800 g



loop

kernmantle
polyamide rope
Ø10,5mm

LB 102 double safety lanyard

EN 354



Ref.: LB 102 xx xx (xx - length)

Standards:

LB 102 10 10 - length 2 x 1,0m

LB 102 15 15 - length 2 x 1,5m

LB 102 20 20 - length 2 x 2,0m

OTHER LENGHTES ON REQUEST

Can be used as:

- safety lanyard with energy absorber.