

## Coalescing Carbon Filters

Use with HPLC cans to minimize odor and capture 99% of liquid particulates released as gaseous vapor. Vent filter snaps conveniently into the quick-disconnect fitting. Carbon filter cartridge color indicator beads change from purple to black when replacement is necessary. Replace the coalescing filter after three or four carbon filter cycles. Meets EPA 40 CFR 264.173.

Description	Attachment/Use With	Model
Coalescing/carbon filter combo with stainless steel fittings	Disconnect cans with stainless steel fittings	28162
Coalescing/carbon filter combo with polypropylene fittings	Disconnect cans with polypropylene fittings	28161

Carbon Filter Replacements	Attachment/Use With	Model
Colometric/carbon filter 3-pack replacements	28162 or 28161 Coalescing/carbon filter	28157

NOTE: When using HPLC carbon filter with FM approved Justrite safety disposal can, the Justrite safety disposal container has not been FM approved or tested in assembly with the HPLC filter attached. However, the container does comply with US OSHA 1910 and NFPA Code 30 requirements, both with and without the HPLC filter. Do not transport safety container while carbon filter is attached.



Filter Replacement Window



## HPLC PTFE Manifold and Compression Fittings

Enables up to six waste lines (per manifold) from HPLC processes to be fed into a single intake fitting. Safety container with manifold installed is OSHA compliant and meets NFPA Code 30. Use on round containers; not for use on oval style can.

Description	Attachment/Use With	Model
PTFE manifold with stainless steel fitting	Containers with stainless steel fittings	28177
PTFE manifold with polypropylene fitting	Containers with polypropylene fittings	28178
PTFE manifold with stainless stacker connector	28177 or 28178	28179
OD 0.0625 in hard wall ETFE tubing compression fittings with ferrules (package of six - blue)		28188
OD 0.125 in hard wall ETFE tubing compression fittings with ferrules (package of six - green)		28189
OD 2 mm hard wall ETFE tubing compression fittings with ferrules (package of six - yellow)		28121
OD 2.5 mm hard wall ETFE tubing compression fittings with ferrules (package of six - orange)		28122
OD 3 mm hard wall ETFE tubing compression fittings with ferrules (package of six - red)		28123


Polytetrafluoroethylene (PTFE) is a synthetic fluoropolymer. Ethylene tetrafluoroethylene (ETFE) is a fluorine based plastic.



28178



28189



Manifold 28177 with stacker 28179 and tubing connector package 28188 and 28189.

## Spill Basin

Durable polyethylene basin keeps work area clean around HPLC cans and captures any inadvertent leakage from HPLC inflow tubes.

Description	W x L x H	Model
5 gallon (19 L)	14.875 x 14.875 x 7.625 (379 x 379 x 194 mm)	84003



84003 with TF12755