

FS-15WS5



FS-15WS5 WELD SHADE 5 MOLDED CYLINDER LEXAN® FACE SHIELD SUPER HARD COAT

Ref. WELFS15WS5_



Product specifications

FS-15WS5 face shield in Weld Shade no. 5 is best suited for welding and high temperature applications. Features a non-proprietary, high quality polycarbonate material that has similar in performance characteristics to Lexan®.

Universal Hole Pattern on Elvex® face shields, also fit on the more popular headgear brands. Elvex® face shields fit to our HG-25 and HG-35 headgears.

Material: Molded Cylinder Polycarbonate

COLOR

Green shade 5

SIZE

No size

Product Use - Risks



Heat



Shock



UV / IR



Agriculture / Green areas
craftman



Construction / Civil engineering



Second work /



Heavy industry



Light industry



Services / Logistics



Hygiene environment



Oil / Gas



Mining



Wind/Energy

Product's highlights & user's benefits

Industry Leading Thickness: 0.078 inches

Die cut universal hole pattern fits most
competitive headgear options.

Heat Tolerance: up to 265 degrees

Dimensions: 8 in. x 15.5 in. x .078 in.

UV Protection: 99.9% between 180-380nm



Certifications and Standards

USA STANDARDS



ANSI Z87.1-2010(+) American National Standards Institute
 ∴ High Velocity Impact
 ∴ High Mass Impact

References

References	Bar code	COLOR	SIZE		
WELFS15WS5	7292946153930	Green shade 5	No size	50	-