



FULL FACE MASKS

C 607



Full face mask with a wide field of vision. One size fits all. Complies with EN 136 (for positive pressure versions complying with EN 148/3 and for use with filter with thread EN 148/1). A silicone rubber version is also available for better comfort and easier decontamination. For use with dust, gas and combined filters (with a threaded connector conforming to EN 148/1) and with air supply devices (with a threaded connector conforming to EN 148/3).

MAIN FEATURES

- Materials used are not likely to cause allergies or irritations to the wearer's skin.
- Good adaptability to most faces.
- Leakage less than 0,05% corresponding to a protection factor of over 2000.
- Wide field of vision, in excess of 72% of the natural field of vision and beyond 93% of the overlapped field of vision.
- Excellent demisting system.
- Breathing resistance (1,8 mbar during inhalation and 2,0 mbar during exhalation at a flow rate of 160 l/min) well below standard approval maximum limits.
- Reduced dead space (less than 50% of maximum allowed).
- Excellent voice transmission thanks to the frontal position of the speech diaphragm, which allows utilization of a telephone, walky-talky and public address device.
- Good flame and radiant heat resistance: the mask is self extinguishing and maintains full protective capacity even after very severe test (approved according to DIN 58646/10).
- Standard visor made of high impact resistance polycarbonate resistant to acids, even at high concentrations.
- Optional: multilayer safety glass visor especially resistant to paints and solvents.
- Quick and easy to don and doff.
- Long storage durability, high resistance to ozone.
- Easy to maintain, clean and sanitize. All components can be disassembled without special tools.
- Compatible with the use of safety helmets.
- Weight: approx. 580 g.

The C607 can be fitted with the following Sèkur filters:

- Series 230 (with screw in adaptor EN 148/1);
- Series DIRIN 230;
- Series DIRIN 300;
- Series DIRIN 500;
- Filter DIRIN 530.

MAIN COMPONENTS

- Synthetic rubber face piece with wide internal seal for a tight fit and adjustable fasteners for the attachment of the harness (patented).
- Wide field of vision and distortion free visor made of polycarbonate, with fiberglass reinforced synthetic resin frame, easily replaceable.
- Inner mask with non return valves.
- Threaded connector conforming with European EN 148/1 standard, with speech diaphragm.
- Two exhalation valves with compensating prechambers.
- Five straps elastic harness made of rubber, with quick release buckles.

CODES

Negative pressure versions:

C 607 E		Cod. 43332034
C 607 E silicone rubber		Cod. 43332037
C 607 F - CL3 (EN 136)		Cod. 43332035

Positive pressure versions:

C 607 SP/A (thread EN 148/3)		Cod. 43333007
C 607 SP/A silicone rubber (thread EN 148/3)		Cod. 43333008

ACCESSORIES

Polycarbonate visor	Cod. 42010230
Multilayer safety glass visor	Cod. 42010235
Frame for prescription lenses	Cod. 42010225
Self adhesive protective films (pack of 10)	Cod. 44323000
Corrugated RM hose with connectors	Cod. 43723127
Carrying case in synthetic resin	Cod. 42010145
Screw-in adaptor for 230 series filters	Cod. 42010600
Disassembling tool	Cod. 42010026

