

Crusader Flex™ Complex Design

- Superior heat resistance with complete protection for hand and wrist.
- Exceptional durability: decisively outperforms 24 oz cotton, hot mill gloves, terry cloth.
- Repeatedly preferred to other hot mill gloves for dexterity, sureness of grip ~ and sheer value for money.



Applications

- Handling hot glass.
- Rubber industry: demoulding rubber tyres, belts and profiles, vulcanising, calendering, etc.
- Demoulding thermoplastics
- Handling hot castings
- Handling hot wooden plates
- Removing sterilised products from autoclaves

Packaging

72 pairs per outer.

Specifications

Ref	Type	Style	EN Size	Length
42-445*	Fully coated	Gauntlet	9, 10	240 mm
42-474	Fully coated	Gauntlet	9, 10	330 mm

Features and Benefits

- » A unique process securely bonds a tough NBR coating to a special loop material.
Excellent resistance to cuts, snags and abrasion.
- » An excellent grip on dry and oily surfaces.
Heat-protective barrier and coating.
- » The back of the hand, forearm and wrist are securely protected from accidental heat hazard (up to 180°C).
Both coating and liner are very flexible.
- » Less tiring to wear. Encourages quicker, more accurate handling.
Asbestos-free.
- » Safer for workers.
Can be washed over and over again.
- » A long-lasting glove that can be re-used many times cuts your costs significantly.
Extremely hard-wearing.
- » In trials, Crusader Flex outwore asbestos by 8:1, terry cloth by 5:1, 24 oz cotton by 4:1.
Sweat-absorbent non-woven felt inner.
- » Permits hot hands to breathe more freely.
No seams in the working area.



2241



X2XXXX

CE 0493

*42-445 size 9, 10: fit for special purpose.

Ansell Occupational Healthcare

- Wijngaardveld 34C, 9300 Aalst, Belgium
Tel +32 (0) 53 71 05 05; Fax +32 (0) 53 71 13 42; Fax Customer Serv. +32 (0) 53 71 01 81
- Brunel Drive, Newark Industrial Estate, Newark, Nottinghamshire NG24 2EG, England, UK
Tel +44 (0) 1636 605 361; Fax +44 (0) 1636 612 845
<http://www.ansell.be> e-mail: info@ansell.com.au



ISO 9002 Certificate
Number FM 40130