



PRODUCT NUMBER: 2232525  
**SHARPFLEX Latex**  
Handling of heavy parts with high cut risks in humid and slippery environment. Light Thermal protection (up to 250°C)

Honeywell

Overview

Reference Number  
2232525

Product Type  
Gloves

Range  
cutandpunctureprotection

Line  
Cut resistant

Brand  
Honeywell

Brand formerly known as  
SPERIAN

Industry

- Automotive and Part Manufacturer
- Aviation
- Building and Construction
- Iron and steel industry
- Logistics

Product Use  
Handling of heavy parts with high cut risks in humid and slippery environment. Light Thermal protection (up to 250°C)

Features & Benefits

Feature  
Knitted glove in composite and para-aramid yarn.

Benefit  
The knitting technique provides the glove with excellent fit and high dexterity.  
The composite yarn is reliable and safe protection.  
The para-aramid yarn assure a resistance to the contact heat and cut risks.

Feature  
Plated polyamide inside

Benefit

Offer a greater comfort and limit the contact of the skin with composite fiber

**Feature**

Blue crinkled latex coating on palm.

**Benefit**

Latex coating provides better grip and a light thermal protection (up to 250°C) resistance

## Technical Description

**Description**

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-03 EEC Basic standards

EN 388-03 Mechanical hazards

EN407-04 : Thermal risks

CHARACTERISTICS :Knitted glove in composite and para-aramid yarn.

Plated polyamide.

Blue crinkled latex coating on palm.

**Product Technology**

Knitted dipped

**Fiber**

Para-aramid and composite

**Gauge**

13

**Glove/liner color**

Yellow and green

**Coating Type**

crinkled latex

**Coating Color**

Blue

**Length**

25 cm

**Harmlessness**

In conformity with the European standards

**Dexterity**

Class 5

**Sizes**

7 to 11

### EN 407 - Heat and/or Fire

Behaviour and/or fire	X
Resistance to contact heat	2
Resistance to convective heat	X
Resistance to radiant heat	X
Resistance to small metal splashes	X
Resistance to molten metal splashes	X

### EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance (Coupe test)	5
Tear resistance	4

Puncture resistance	2
---------------------	---

## Packaging Label

### Tagging

CE HONEYWELL  
2232525 XX  
EN 420  
EN 388 : 3542  
EN 407 : X2XXXX

## Certifications

### E.C. Declaration of Conformity

#### EC Category PPE

2

#### EC Certificate Number

0075/797/162/06/12/0492

#### EC Attestation

EC Attestation

#### EC Attestation Number

0075/797/162/06/12/0492

## Additional Information

### User Manual

UI 106

### User Information Sheet

106

## Maintenance

### Storage Information

Minimum packaging 10 pairs.

Cartons of 100 pairs.

### Care Instructions

This article can be cleaned. For cleaning instructions please contact Honeywell safety products