

# PRODUCT NUMBER: 2012897 **OVERGLOVE LT 2,5/5 Kv**

Article designed for the mechanical protection of low voltage 2.5kV electrician's gloves (Electrosoft glove 20 919 03) and 5 KV (Electrosoft glove 20 919 07).

# Honeywell

# **Overview**

#### **Reference Number**

2012897

### **Product Type**

Gloves

#### Range

**Electrical Protection** 

### Line

Overgloves

#### **Brand**

Honeywell

#### Brand formerly known as

**SPERIAN** 

### Industry

• Energy or Electricity Maintenance

Services

Telecoms

#### **Product Use**

Article designed for the mechanical protection of low voltage 2.5kV electrician's gloves (Electrosoft glove 20 919 03) and 5 KV (Electrosoft glove 20 919 07).

# **Features & Benefits**

#### **Feature**

Yellow cowhide grain leather overglove Water-repellent and silicone treatment Gunn cut, thumb in one piece, gauntless Velcro adjustment strap on the back 150 mm split leather cuff sewed outside

# Benefit

COMFORT

The Velcro fastening tab provides the glove with good support.

#### OVERGLOVE LT 2,5-5 Kv - 2012897

#### RESISTANCE

The cowhide silicone grain leather ensures good flexibility, water repellency as well as good mechanical protection. Protects Electrosoft gloves against risks of cuts and tearing.

# **Technical Description**

#### Description

CE CATEGORY: II Intermediary risks In accordance with standards: EN 420-03 EEC Basic standard EN 388-03 Mechanical risks

#### CHARACTERISTICS:

Yellow cowhide grain leather overglove Water-repellent and silicone treatment Gunn cut, thumb in one piece, gauntless Velcro adjustment strap on the back 150 mm split leather cuff sewed outside

#### **Product Technology**

Cut and Sewn

#### Glove/liner color

Yellow

#### **Coating Type**

Leather

#### Length

31,5 cm

#### **Thickness**

Palm: 0,8/1,1 mm - Cuff: 1,3/1,5

#### Harmlessness

In conformity with the European standards

### Dexterity

Class 5

#### Sizes

8 to 11

# EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	2
Cutting resistance (Coupe test)	1
Tear resistance	2
Puncture resistance	1

# **Packaging Label**

### **Tagging**

CE SPERIAN 2012898 XX EN 420

EN 388: 2121

# **Certifications**

E.C. Declaration of Conformity

**EC Category PPE** 

2

### **Quality Assurance**

ISO 9001 / 2000

**EC Certificate Number** 

# OVERGLOVE LT 2,5-5 Kv - 2012897

0075/797/162/12/06/0355

**EC** Attestation

EC Attestation

**EC Attestation Number** 

0075/797/162/12/06/0355 EXT 03/02/07

# **Additional Information**

**User Manual** 

UI 102

**User Information Sheet** 

102

# **Maintenance**

**Storage Information**Minimum packaging 10 pairs. Cartons of 50 pairs.

**Care Instructions** 

In order to keep its properties, this article should not be cleaned.

© Honeywell International Inc.