



PRODUCT NUMBER: 2012899  
**OVERGLOVE LT 30 Kv**

Article designed for the mechanical protection of electrician's gloves for high voltage work: 20 KV (Electrosoft glove 20 919 21) and 30 KV (Electrosoft glove 20 919 31).

Honeywell

Overview

**Reference Number**  
2012899

**Product Type**  
Gloves

**Range**  
Electrical Protection

**Line**  
Overgloves

**Brand**  
Honeywell

**Brand formerly known as**  
SPERIAN

**Industry**

- Energy or Electricity
- Maintenance
- Services
- Telecoms

**Product Use**  
Article designed for the mechanical protection of electrician's gloves for high voltage work: 20 KV (Electrosoft glove 20 919 21) and 30 KV (Electrosoft glove 20 919 31).

Features & Benefits

**Feature**  
Yellow cowhide grain leather overglove  
Water-repellent and silicon treatment  
Gunn cut, thumb in one piece, gauntless  
Velcro® adjustment strap on the back  
150 mm split leather cuff sewed outside

**Benefit**  
COMFORT  
The Velcro® fastening tab provides the glove with good support.

**RESISTANCE**

The cowhide silicone grain leather ensures good flexibility, water repellency as well as good mechanical protection.  
Protects Electrosoft gloves against risks of cuts and tearing.

## Technical Description

**Description**

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-2003 EEC Basic standards

EN 388-2003 Mechanical hazards

**CHARACTERISTICS :**

Yellow cowhide grain leather overglove

Water-repellent and silicon treatment

Gunn cut, thumb in one piece, gauntless

Velcro® adjustment strap on the back

150 mm split leather cuff sewed outside

**Product Technology**

Dipped Gloves

**Glove/liner color**

Yellow

**Coating Type**

Leather

**Length**

31,5 cm

**Thickness**

Palm : 0,8/1,1 mm - Cuff : 1,3/1,5

**Harmlessness**

In conformity with the European standards.

**Dexterity**

Class 5

**Sizes**

8 to 11

### EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	2
Cutting resistance (Coupe test)	1
Tear resistance	2
Puncture resistance	1

### Packaging Label

**Tagging**

CE SPERIAN

2012899 XX

EN 420

EN 388 : 2121

## Certifications

**E.C. Declaration of Conformity****EC Category PPE**

2

**Quality Assurance**

ISO 9001 / 2000

**EC Certificate Number**

0075/797/162/12/06/0355

**EC Attestation**

EC Attestation

**EC Attestation Number**

0075/797/162/12/06/0355

## Additional Information

**User Manual**

UI 102

**User Information Sheet**

102

## Maintenance

**Storage Information**

Minimum packaging 10 pairs.

Cartons of 50 pairs.

**Care Instructions**

In order to keep its properties, this article should not be cleaned.