



**PRODUCT NUMBER: 2032681**

## **ARATHERMA COMFORT**

For handling of sharp and hot objects in a dry atmosphere. Glass industry and paper. Automobiles, car equipment manufacturers.

**Honeywell**

### Overview

**Reference Number**

2032681

**Product Type**

Gloves

**Range**

Thermal Protection

**Line**

Heat

**Brand**

Honeywell

**Brand formerly known as**

SPERIAN

**Industry**

- Industry
- Automotive and Part Manufacturer
- Glass Industries
- Iron and steel industry

**Product Use**

For handling of sharp and hot objects in a dry atmosphere. Glass industry and paper. Automobiles, car equipment manufacturers.

### Features & Benefits

**Feature**

100 % Kevlar® knitted glove

Lined with 100% cotton knitted glove

150 mm green fireproofed canvas cuff

Ambidextrous

**Benefit**

COMFORT

The knitting technique helps to obtain a glove that conforms snugly to the hand and good dexterity.

The glove offers maximum comfort and added sturdiness.

Kevlar® glove lined with a cotton glove, pleasant to the touch.

The reinforced lining enhances the glove's mechanical performance while absorbing perspiration.  
 It is ambidextrous and thus more cost-effective.  
 The glove's relative thickness (gauge 7) helps to absorb shocks, making it suitable for the handling of heavy objects.

**RESISTANCE**

The Kevlar® fibre offers good resistance to cuts and protection against thermal hazards (contact heat).  
 Glove endowed with a fire retardant canvas (150mm), thus extending protection of the forearm.  
 Withstands 18.5 seconds at 250°C and 13.3 seconds at 350°C

## Technical Description

**Description**

CE CATEGORY : II Intermediary risks  
 In accordance with standards :  
 100 % Kevlar® knitted glove  
 Lined with 100% cotton knitted glove  
 150 mm green fireproofed canvas cuff  
 Ambidextrous

**Product Technology**

Knitted

**Gauge**

7

**Coating Type**

Kevlar®

**Length**

37 cm

**Harmlessness**

In conformity with the European standards

**Dexterity**

Class 2

**Sizes**

Unique size

### EN 407 - Heat and/or Fire

Behaviour and/or fire	4
Resistance to contact heat	3
Resistance to convective heat	X
Resistance to radiant heat	X
Resistance to small metal splashes	X
Resistance to molten metal splashes	X

### EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	1
Cutting resistance (Coupe test)	4
Tear resistance	3
Puncture resistance	X

### Packaging Label

**Tagging**

CE HONEYWELL  
 2032681 XX  
 EN 420

EN 388 : 143X  
EN 407 : 43XXXX

## Certifications

### E.C. Declaration of Conformity

#### EC Category PPE

2

#### EC Certificate Number

0075/797/162/09/08/0326

#### EC Attestation

EC Attestation

#### EC Attestation Number

0075/797/162/09/08/0326

## Additional Information

### User Manual

UI 106

### User Information Sheet

106

## Maintenance

### Storage Information

Minimum packaging 10 pairs.

Cartons of 50 pairs.

### Care Instructions

In order to keep its properties, this article should not be cleaned.