



PRODUCT NUMBER: 2281561

FIREMAN

Heat resistant glove (formerly used as glove for firemen)

Honeywell

Overview

- Reference Number
- 2281561
- Product Type
- Gloves
- Range
- Specific Protection
- Brand
- Honeywell
- Brand formerly known as
- SPERIAN
- Industry
- Industry

• Army - Defence

• Fire Protection brigades
- Product Use
- Heat resistant glove (formerly used as glove for firemen)

Features & Benefits

- Feature
- Yellow water repellent cowhide grain leather glove

Gunn cut, winged thumb, gauntlet type

Hand lined with Kevlar®/cotton jersey

Water repellent grain leather yoke at the base of thumb and middle finger

Veins protection

Split leather cuff

Velcro strap

Stitch with Kevlar® thread
- Benefit
- COMFORT

US assembly.

Elasticated, with a fastening tab, the glove offers good support.

Hand lined with Kevlar® cotton jersey for a better comfort of use.

RESISTANCE

The silicone, water repellent cowhide grain leather ensures good flexibility at a low temperature, resisting water and offering good mechanical protection.

The Kevlar® cotton lining provides protection against cuts and thermal hazards.

The Kevlar® thread assembly ensures sturdy resistance of the seams with regard to the heat and wear, while offering the best possible thermal insulation.

Technical Description

Description

CE CATEGORY : III Irreversible risks

In accordance with standards :

EN 420-2003 EEC Basic standards

EN 388-2003 Mechanical hazards

EN 407-2004 Thermal hazards

CHARACTERISTICS :

Yellow water repellent cowhide grain leather glove

Gunn cut, winged thumb, gauntlet type

Hand lined with Kevlar®/cotton jersey

Water repellent grain leather yoke at the base of thumb and middle finger

Veins protection

Split leather cuff

Velcro strap

Stitch with Kevlar® thread

Product Technology

Cut and Sewn

Coating Type

Leather, Kevlar® and cotton

Thickness

1.1/1.3 mm

Harmlessness

In conformity with the European standards

Dexterity

Class 5

Sizes

7 to 11

EN 407 - Heat and/or Fire

Behaviour and/or fire	4
Resistance to contact heat	1
Resistance to convective heat	3
Resistance to radiant heat	2
Resistance to small metal splashes	X
Resistance to molten metal splashes	X

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance (Coupe test)	2
Tear resistance	2
Puncture resistance	2

Packaging Label

Tagging

CE HONEYWELL
2281561 XX
EN 420
EN 388 : 3222
EN 407 : 4132XX

Certifications

E.C. Declaration of Conformity

EC Category PPE

2

EC Certificate Number

0075/797/162/12/09/0517

EC Attestation

EC Attestation

Additional Information

User Manual

UI 106

User Information Sheet

106

Maintenance

Storage Information

Minimum packaging 10 pairs.

Cartons of 50 pairs.

Care Instructions

In order to keep its properties, this article should not be cleaned.