



PRODUCT NUMBER: 2054044  
**WELDER HR**  
MIG and ARC welding.

Honeywell

Overview

**Reference Number**  
2054044

**Product Type**  
Gloves

**Range**  
Thermal Protection

**Line**  
Heat

**Brand**  
Honeywell

**Brand formerly known as**  
SPERIAN

**Industry**

- Automotive and Part Manufacturer
- Foundry
- Iron and steel industry
- Metal steel
- Ship Building
- Transportation
- Utilities
- Welding

**Product Use**  
MIG and ARC welding.

Features & Benefits

**Feature**  
Heat-resistant cowhide split leather glove  
US assembly, winged thumb and reinforced index finger  
Cuff, 150mm  
Kevlar® thread seams

**Benefit**  
COMFORT  
Its leather is ideal for welders' gloves.  
The US assembly, winged thumb and flexible materials used make this glove anatomical, thus providing excellent comfort for use.

**RESISTANCE**

Split leather treated against the heat for excellent resistance to contact and radiant heat.

The Kevlar® thread assembly ensures sturdy seams with respect to the heat and wear as well as better thermal insulation.

**SAFETY**

The split leather cuff protects a large part of the forearm against mechanical hazards.

## Technical Description

**Description**

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-2003 EEC Basic standards

EN 388-2003 Mechanical hazards

EN 407-2004 Heat hazards

**CHARACTERISTICS :**

Heat-resistant cowhide split leather glove

Gunn cut, winged thumb, seamless forefinger

150 mm cuff

Stitch with Kevlar® thread

**Coating Type**

Cuir

**Length**

36 cm

**Thickness**

Palm 1,1/1,3 mm - Cuff 1,3/1,5 mm

**Harmlessness**

In conformity with the European standards

**Dexterity**

Class 5

**Sizes**

8 to 11

### EN 407 - Heat and/or Fire

Behaviour and/or fire	4
Resistance to contact heat	1
Resistance to convective heat	3
Resistance to radiant heat	1
Resistance to small metal splashes	4
Resistance to molten metal splashes	X

### EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	4
Cutting resistance (Coupe test)	1
Tear resistance	2
Puncture resistance	2

### Packaging Label

**Tagging**

CE HONEYWELL  
20540044 XX  
EN 420  
EN 388 : 4122  
EN 407 : 41314X

## Certifications

### E.C. Declaration of Conformity

#### EC Category PPE

2

#### EC Certificate Number

0075/797/162/10/13/1088

#### EC Attestation

EC Attestation

#### EC Attestation Number

0075/797/162/10/13/1088

## Additional Information

### User Manual

UI 106

### User Information Sheet

106

## Maintenance

### Storage Information

Minimum packaging 10 pairs.

Cartons of 50 pairs.

### Care Instructions

In order to keep its properties, this article should not be cleaned.