



PRODUCT NUMBER: 1004579
**ME06 Shock Absorbing
 Lanyard - 2m - ML04+CS20**

Honeywell
MILLER™

Overview

Reference Number

1004579

Product Type

Fall Protection

Range

Shock Absorbing Lanyards

Brand

Miller by Honeywell

Industry

- Industry
- Building and Construction

Product Use

2 m webbing shock absorbing lanyard equipped with a 63mm opening scaffold hook ML04 and a screwgate karabiner CS20

Features & Benefits

Feature

Adapted to harsh work conditions and difficult work environments. The lanyards offer a better comfort in case of a fall. Small size tear off dissipating element, which reduces the weight and makes the lanyard easier to handle and carry. Come with a variety of attachments and designed to better meet fall protection needs.

Benefit

Made of a highly resistant and durable 23mm polyester webbing or 12mm Polyamid rope for increased durability.

Technical Description

Weight

0.930 kg

Breaking Strength

> 15 KN

Operating Temperature

-30°C to +50°C

Webbing

Webbing Raw Material

Polyester

Webbing Breaking Strength

> 3000 daN

Connector

Connector Type

TypeScrewgate

Connector Raw Material

Raw MaterialZinc-plated steel

Connector Opening

Opening18mm

Connector Breaking Strength

Breaking Strength> 2500 daN

Connector Standard

StandardEN 362

Energy Absorber

Energy Absorber Raw Material

Polyamide 30mm

Energy Absorber Breaking Strength

for linked element: > 3200 daN,for unlinked element: > 1500 daN

Complementary Information

Automatic snap hook ML04 Raw material: White chromate steel Standard: EN 362 Opening : 63 mm Breaking strength: > 2200 daN

Certifications

E.C. Declaration of Conformity

EC Category PPE

3

EC Certificate Number

333

EC Attestation

EC Attestation

EC Attestation Number

0082/490/160/04/00/0144

Additional Information

User Manual

NT90004208 IND L

User Information Sheet

User manual

Packaging

EAN Code

7312550045794