

Miller 201RLS Non-Shock-Absorbing Rope Lanyard

Description

The 201RLS is a non-shock-absorbing rope lanyard designed for positioning and restraint applications. It is available in lengths from 4-600 feet. The 201RLS is available in five unique midels that utilize different rope diameters with either nylon or polyester rope.

Materials

Rope Designations by Model:

- 201RLS-2 5/8" Spun Nylon
- 201RLS-3 3/4" Filament Nylon
- 201RLS-4 1/2" Filament Polyester
- 201RLS-5 5/8" Filament Polyester
- 201RLS-8 1/2" Filament Nylon

Minimum Tensile:5000 lbs. on each ropeHardware:Steel minimum tensilestrength

Locking Snap Hooks 5,000 lbs. (22kN)

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Splices: A standard four-tuck splice is hand-crafted on each end with a tensile strength equal to that of the rope. The ends of the rope are seared to prevent fraying. The last splice is treated with a nylon-based stiffening agent to prevent the splice from unraveling. **Thimbles:** A round, bright yellow plastic thimble is used in each lanyard eye to protect the eye from wear.

Technical

Max. Weight Load: 310 lbs (140.62 kg)

Certifications

Meets OSHA: 1926.502, 1910.66; ANSI: A10.14, Z359.1; and CSA: Z259.2.2 Type 1 requirements.

Sizes Available

All models listed above are available in lengths from 4' to 600'. Sizes less than 30 ft. can be ordered in 1-ft. increments. Sizes 30 ft. and above, must be ordered in 5-ft. increments.

WARNING: This product is to be used for positioning only, unless it is used in conjunction with a shock absorber.

Limitless Possibilities. Ask the Expert. Technical Service: 800.873.5242 www.millerfallprotection.com

Honeywell Industrial Safety 900 Douglas Pike Smithfield, RI 02917

USA Phone: 800.430.5490 Fax: 800.322.1330 Canada Phone: 888.212.7233 Fax: 888.667.8477 WARNING! This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.

