









**Product Family**  
**Söll Xenon® 2.0 Horizontal Lifeline System**

Söll Xenon® 2.0 HLL is an innovative height safety solution that **conforms to new EN795:2012 standards and regulations.**

It's a high quality, durable system made of corrosion resistant stainless steel and is ideally suited to industrial applications like working on crane runways, loading bays and roofs.



**Product Numbers & Ordering Information**

	Product Numbers	Details
	27466 / 1030225	<b>Söll Xenon Standard Shuttle</b>
	26940 / 1032530	<b>Söll Xenon Overhead Wheeled Trolley</b>
	26266 / 1031960	<b>Shock-Absorber – 8 mm</b>
	26267 / 1031961	<b>Shock-Absorber swageless – 8 mm</b>
	26268 / 1031962	<b>Shock-Absorber with Eyebolt – 8 mm</b>
	23496 / 1010609	<b>Söll Xenon universal intermediate hanger</b> stainless steel 316 – 8 mm



25141 / 1019004

**Söll Xenon intermediate**  
all stainless steel 316 cable guide - 8 mm



23510 / 1010612

**Intermediate hanger**  
for bendings till 45° - 8 mm



26350 / 1031701

**Söll Xenon-Intermediate bracket**  
for use in overhead-systems, flexible, for cable-diameter 8 mm only



2609 / 1006701

**Cable End Swage**  
accommodates 8mm cable.



23500 / 1010550

**Swage cable end**  
accommodates 8mm cable with tensioner.



26367 / 1031700

**Swageless cable end**  
8 mm




23938 / 1013722

**Swageless cable end**  
part with tensioner - 8 mm



23820 / 1006772

**Söll Xenon HLL identification plate**  
English, French, German, Dutch



24122 / 1028190

**Söll Xenon HLL identification plate**  
Portuguese, Italian, Greek, Spanish




24215

**Söll Xenon HLL identification plate**  
Finnish, Swedish, Icelandic, Danish



24597

**Söll Xenon HLL identification plate**  
Polish, Slovak, Hungarian, Czech



25315

**Söll Xenon HLL identification plate**  
English, Bulgarian, Serbian, Romanian



22611 / 1006704

**8 mm cable swage for cable extension**



22631 / 1006178

**End anchor parts**



27128 / 1033020

**End anchor eye 360° turnable - M16x40**



22636 / 1006062

**90° angle kit - 8 mm**



22007 / 1006294

**Bending kit - 8 mm**



23806 / 1012621

**Söll Xenon-Curve 90° with single fixation point**  
8 mm



25749 / 1029390

**Xenon-Overhead-Curve 90° internal**



25750 / 1029391

**Xenon-Overhead-Curve 90° external**



22613 / 90002534

**Ø 8mm - 7x7 Stainless steel cable - the meter**



23117 / 1007911

**Ø 8mm - 7x7 Stainless steel cable - 250m coil**



22614 / 1006770

**Ø 8mm - 7x7 Stainless steel cable - 500m coil**



24856 / 90014646

**Ø 8 mm - 1x19 Stainless steel cable - the meter**




24745 / 1017310

**Interfix 260-320 mm**  
incl. 16 rivets & seal tape ... [Please order additionally: Anchorage Eye (24863) for use as single anchorage point OR Rivet kit (28083) and junction plate (24862) for use as end anchor point]



24746 / 1017313

**Interfix 321-500 mm**  
incl. 16 rivets & seal tape ... [Please order additionally: Anchorage Eye (24863) for use as single anchorage point OR Rivet kit (28083) and junction plate (24862) for use as end anchor point]



24749 / 1017317

**Interfix 200-400 mm**

incl. clamps ... [Please order additionally: Anchorage Eye (24863) for use as single anchorage point OR Junction plate (24862) for use as end anchor point]



24750 / 1017330

**Interfix 300-600 mm**

incl. clamps ... [Please order additionally: Anchorage Eye (24863) for use as single anchorage point OR Junction plate (24862) for use as end anchor point]



24862 / 1017333

**Junction plate for use as an end anchor**

**Overview**

**Key Features**

The Söll Xenon® 2.0 Horizontal Lifeline System ensures that structural damage is prevented in case a fall occurs. The system also doubles as an anchorage point to easily rescue workers should they fall. The Horizontal Lifeline System incorporates a unique, state-of-the-art shock absorber, which uses patented Miller 'Force-dispersal Technology' to provide fall protection for up to seven workers across a maximum span of 20m (1x19 cable, 8mm wide), depending on the line configuration.

**The shock absorber takes the strain**

The Söll Xenon multifunction shock absorber has been designed to disperse energy during a fall to protect both workers and the structure. Its patented 'Force-dispersal Technology' ensures that energy is distributed evenly when the shock absorber is deployed. The four-in-one device incorporates a tension indicator, a cable tensioner, an energy absorber and a fall indicator. Tensioning is quick and easy to do by rotating the shock absorber horizontally. Only one energy absorber is necessary for all installations, irrespective of whether it's an overhead or standard installation (on posts or against walls). The device is available with or without swages to suit the equipment available for installation.

**Söll Xenon® automatic pass through shuttles**

The ergonomically designed Miller shuttle self-aligns for smooth passthrough of intermediate and corner brackets. A double-locking mechanism ensures the shuttles are secure yet can still be operated with one hand.

**Söll Xenon® intermediate brackets**

These versatile brackets can be configured as free-floating, springloaded or locked. As the brackets are assembled on the cable it means they can easily be replaced.

**ATEX certified Söll Xenon® overhead application**

An appropriate selection of SKUs for an overhead installation of the Söll Xenon system has been additionally certified to be used in potentially explosive atmospheres (according to Directive 94/9/EC).

**Recommended Industries/Use**

- Construction

**Hazards**

- Fall from height

**Regulations**

- Meets EN 795:2012 standard (and all applicable OSHA, ANSI and AS/NZS standards)

**Warranty Information**

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested

to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our warranty does not apply to abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our warranty of one year after delivery, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at +33 248 53 08 97 (Southern Europe) or +49 9281 8302 0 (Northern Europe). Manufacturing specifications are subject to change without notice.

## Certifications

### Conformity licence Söll Xenon EN\_2014

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Permanent\\_Anchorage\\_Systems/4294987897/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Permanent_Anchorage_Systems/4294987897/1033.aspx)

Conformity licence Söll Xenon

### Declaracion de conformidad Söll Xenon ES\_2014

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Permanent\\_Anchorage\\_Systems/4294988018/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Permanent_Anchorage_Systems/4294988018/1033.aspx)

Spain : Declaracion de conformidad Söll Xenon

### Conformity licence Söll Xenon NL\_2014

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Permanent\\_Anchorage\\_Systems/4294987901/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Permanent_Anchorage_Systems/4294987901/1033.aspx)

Netherlands and Belgium : Conformiteitsverklaring Söll Xenon

### Söll Xenon ATEX Certificate

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Permanent\\_Anchorage\\_Systems/4294984773/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Permanent_Anchorage_Systems/4294984773/1033.aspx)

ATEX Certificate Söll Xenon overhead

## Literature & Documents

### HONE130300125\_Brochure Söll Xenon UK page by page

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/4294974889/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/4294974889/1033.aspx)

Söll Xenon brochure

### Soell Xenon User Manual

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Temporary\\_Anchorage\\_Connectors/4294974550/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Temporary_Anchorage_Connectors/4294974550/1033.aspx)

Söll Xenon assembly, installation and operating instruction

## Training & Proper Use

Söll Xenon is only available for Miller trained professional installers.

Proper product training and professional fall protection training is required.

Refer to Product Use Instructions enclosed with products.

## Additional Information

France, Spain, Portugal, North Africa : +33 248 53 08 97 and email : [lignedevie.hsp@honeywell.com](mailto:lignedevie.hsp@honeywell.com)

Northern and Central Europe, Italy : +49 9281 8302 0 and email : [scs-hof@honeywell.com](mailto:scs-hof@honeywell.com)

## Technical Support

France, Spain, Portugal, North Africa : +33 248 53 08 97 and email : [lignedevie.hsp@honeywell.com](mailto:lignedevie.hsp@honeywell.com)

Northern and Central Europe, Italy : +49 9281 8302 0 and email : [scs-hof@honeywell.com](mailto:scs-hof@honeywell.com)