Honeywell | Safety Products

USA

Contraction of the second s

Product Family Miller Manyard HP Shock-Absorbing Lanyards

Absorbing Lanyards With 20 years of design refinement, the "Original" Miller Manyard HP[™] Shock-Absorbing Lanyards are unsurpassed in the market.

Visit MillerFallProtection.com >



Q

Product Numbers & Ordering Information

	Product Numbers	Details
	216TC/4FTGN	High Performance Shock-Absorbing Webbing 4-ft. single leg; 1 locking snap hook and carabiner
	216TC/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. single leg; 1 locking snap hook and carabiner
₩48₽ #£#8	216TO/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. single leg; 2 locking snap hooks and "O" ring extension
⇔.a.a.ø # % m ()	216TO-Z7/6FTGN	ANSI Z359-2007 Compliant with High Performance Webbing 6-ft. single leg; 2 locking snap hooks and "O" ring extension
≈ - 6 .e # t t t []	216TWDLS/4FTBL	High Performance Shock-Absorbing Webbing 4-ft. single leg; 2 locking snap hooks; blue
ť0.0 ¢€₩[]	216TWDLS/6FTBL	High Performance Shock-Absorbing Webbing 6-ft. single leg; 2 locking snap hooks; blue
a.a.≠ * € *± ()	216TWLS/4FTGN	High Performance Shock-Absorbing Webbing 4-ft. single leg; 2 locking snap hooks

Page 1 of 5 © Honeywell International Inc.

		Miller Manyard HP Shock-Absorbing Lanyards
	216TWLS/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. single leg; 2 locking snap hooks
	216TWLS/9FTGN	High Performance Shock-Absorbing Webbing 9-ft. single leg; 2 locking snap hooks
(=+8≠ ≠€±80	216TWLS- Z7/6FTGN	ANSI Z359-2007 Compliant with High Performance Webbing 6-ft. single leg;2 locking snap hooks
₩6.20 ₩6.20	216WAL/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. single leg; 2 aluminum locking snap hooks
₩6.0# #6.128	219TWDRS/6FTBL	High Performance Shock-Absorbing Webbing 6-ft. single leg; 1 locking snap hook and 1 (2-1/2 in.) locking rebar hook; blue
₩6.0# #6.128	219TWRS/4FTGN	High Performance Shock-Absorbing Webbing 4-ft. single leg; 1 locking snap hook and 1 (2-1/2 in.) locking rebar hook
₩6.0# #6.128	219TWRS/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. single leg; 1 locking snap hook and 1 (2-1/2 in.) locking rebar hook
₩6.0# #6.128	219TWRS- Z7/6FTGN	ANSI Z359-2007 Compliant with High Performance Webbing 6-ft. single leg; 1 locking snap hook and 1 (2-1/2 in.) locking rebar hooks
(= 4 A # # € # []	219WAL/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. single leg; 1 aluminum locking snap hook and 1 (2-1/4 in.) aluminum locking rebar hook
(~*A# #€##{	231TWRS/4FTGN	High Performance Shock-Absorbing Webbing 4-ft. double leg; 1 locking snap hook and 2 (2-1/2 in.) locking rebar hooks
(~*A# #€##{	231TWRS/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. double leg; 1 locking snap hook and 2 (2-1/2 in.) locking rebar hooks
(=+68≠ ≠€#8₿	231TWRS- Z7/6FTGN	ANSI Z359-2007 Compliant with High Performance Webbing 6-ft. double leg; 1 locking snap hook and 2 (2-1/2 in.) locking rebar hooks
-101 +140	231WAL/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. double leg; 1 aluminum locking snap hook and 2 (2-1/4 in.) aluminum locking rebar hooks

		Miller Manyard HP Shock-Absorbing Lanyards
₩400 #840	232TWLS/5FTGN	High Performance Shock-Absorbing Webbing 5-ft. double leg; 3 locking snap hooks
(⇒+0⊅ ≠€₩₿	232TWLS/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. double leg; 3 locking snap hooks
(⇒+6⊅ ≠€∰₿	232TWLS- Z7/6FTGN	ANSI Z359-2007 Compliant with High Performance Webbing 6-ft. double leg; 3 locking snap hooks
(=+6.0 ≠€±₿	232WAL/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. double leg; 3 aluminum locking snap hooks
(== de fi # 	233TWLS/6FTGN	High Performance Shock-Absorbing Webbing 6-ft single leg; 1 locking snap hook and 1 choke-off loop
(===0.0 ≠€±1.0	233TWLS- Z7/6FTGN	ANSI Z359-2007 Compliant with High Performance Webbing 6-ft single leg; 1 locking snap hook and 1 choke-off loop
(=+0⊅ ≠€₩₿	233TWRS/6FTGN	High Performance Shock-Absorbing Webbing 6-ft single leg; 1 locking rebar hook (2-1/2 in.) and 1 choke-off loop
(=+0≠ ≠€±₿	233TWRS/8FTGN	High Performance Shock-Absorbing Webbing 8-ft single leg; 1 locking rebar hook (2-1/2 in.) and 1 choke-off loop
(=+0≠ ≠€±₿	233WAL/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. single leg; 1 aluminum locking snap hook and 1 choke-off loop
(=+6.0 ≠€±₿	233WRAL/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. single leg;1 aluminum locking rebar hook (2-1/4 in.) and 1 choke-off loop
(==== () ● € == ()	266TWLS/4FTGN	High Performance Shock-Absorbing Webbing 4-ft. double leg; 2 locking snap hooks and 1 choke-off loop
(= 0.0 € € 11 ()	266TWLS/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. double leg; 2 locking snap hooks and 1 choke-off loop
(=+60.0 ♥≤=0	266TWO/4FTGN	High Performance Shock-Absorbing Webbing 4-ft. double leg; 2 locking snap hooks and "O" ring extension

Miller Manyard HP Shock-Absorbing Lanyards

₩48# #8#8	266TWRS/4FTGN	High Performance Shock-Absorbing Webbing 4-ft. double leg; 2 locking rebar hooks (2-1/2 in.) and 1 choke-off loop
	266TWRS/6FTGN	High Performance Shock-Absorbing Webbing 6-ft. double leg; 2 locking rebar hooks (2-1/2 in.) and 1 choke-off loop

Overview

Key Features

- · Specially-woven shock-absorbing inner core smoothly expands out, reducing fall arrest forces
- Unique warning flag provides visual proof that a lanyard has been involved in a fall and must be removed from service
- Heavy-duty tubular outer jacket serves as a back-up lanyard
- Aluminum models available

Recommended Industries/Use

Construction
Manufacturing

Hazards

Confined Space
Fall from height

Regulations

· Meets all applicable OSHA, ANSI and CSA standards

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

Specification Sheets

• For full engineering specification sheets, go to Literature & Documents

Literature & Documents

Miller Aluminum Hooks Brochure - US http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Lanyards /20604/1033.aspx

Learn more about Miller's Lightweight Aluminum Hooks

Miller Lanyards & Shock Absorbers Manual - US http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Lanyards /15861/1033.aspx

Miller Lanyards & Shock Absorbers Instruction Manual

SP434 Manyard HP Aluminum Spec Sheet - US http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Lanyards /24951/1033.aspx

> Page 4 of 5 © Honeywell International Inc.

Miller Manyard HP Shock-Absorbing Lanyards

SP434 Manyard HP (Aluminum Models) Specification Sheet

SP449 Manyard HP Spec Sheet_US http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Lanyards /42895/1033.aspx

SP449 Manyard HP Specification Sheet

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 or 814/423-2118 email: millertechexpert@sperian.com

Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperian.com

RELATED PRODUCTS

© Honeywell International Inc.