








Product Family

Miller ManHandler Hoist/Winch

The Miller ManHandler Hoist is the perfect solution for a range of applications including confined space entry, rescue, positioning and personnel/material handling.



Product Numbers & Ordering Information

	Product Numbers	Details
	8280H/YL	SRL Carrying Bag Carrying bag for hoist, winch or self-retracting lifeline (SRL)
	8442/65FT	ManHandler Personnel-Rated Hoist with Galvanized Steel Wire Rope (3/16-in.) 65-ft; Mounting Bracket; Pulley; Carabiner; For personnel positioning, confined space entry, and rescue. A secondary fall arrest system is recommended for fall protection.
	8442SS/100FT	ManHandler Personnel-Rated Hoist System w/Stainless Steel Wire Rope (3/16") 100-ft; Mounting Bracket; Pulley; Carabiner.
	8442SS/65FT	ManHandler Personnel-Rated Hoist System w/Stainless Steel Wire Rope (3/16") 65-ft; Mounting Bracket; Pulley; Carabiner
	8442-Z7/65FT	ManHandler Personnel-Rated Hoist with Galvanized Steel Wire Rope (3/16-in.) 65-ft; Galvanized Steel Wire Rope [3/16"] Hoist; Mounting Bracket; ANSI Z359-2007 Compliant

Overview

Key Features

For daily personnel/material handling activities

A secondary fall arrest system is recommended for fall protection.

- Compact, durable steel construction

- Smooth, controlled winding action
- Effortless lifting and lowering with 5:1 gear ratio
- Anti-backlash crank handle braking system prevents freewheeling
- Built-in mounting bracket

Recommended Industries/Use

- Government
- Mining
- Municipal Services

Hazards

- Confined Space
- Fall from height

Regulations

- Meets all applicable OSHA, ANSI and CSA standards

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

Maximum Working Capacity

- 350 lbs (1.6kN)

Specification Sheets

- For full engineering specification sheets, go to downloads and documentation

Literature & Documents

Miller ManHandler Instruction Manual - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Confined_Space/23952/1033.aspx

Miller ManHandler Instruction Manual

SP369 ManHandler Spec Sheet - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Confined_Space/23953/1033.aspx

SP369 ManHandler Spec Sheet

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperianprotection.com

RELATED PRODUCTS

© Honeywell International Inc.