

## Miller Permanent Roof Anchor RA41/

### Description

The Miller RA41/, Single D, Permanent Roof Anchor is designed to provide fall protection on rooftops. The anchor can be applied during new construction or retrofitted into the design of finished roofs with asphalt shingles, shakes or tiles. The Single D is nailed securely across the ridge opening and the roof is finished, overtop of the Single D, with the roofing materials and ridge vent. Only the D-rings are left exposed for a quick and safe connection. The Single D is also ideal for use on wall mount applications to provide fall protection.

### Materials

**Stamping:** Type 304 stainless steel  
(20 gauge - .035 in.)  
**D-Ring:** Zinc plated steel  
**Nails:** 8 - Galvanized steel (16d)

\*Must be used in conjunction with a shock-absorbing lanyard that will limit fall arrest forces to 900 lbs.

### Technical

**Weight:** 1.50 lbs. (0.68 kg)  
**Max Working Load:** 310 lbs. (140.62 kg)

### Certification

Meets all OSHA 1926.502 requirements.

**Ideal for use on residential roofs for the following:**

- **Gutter cleaning**
- **Window/Skylight Cleaning**
- **Trimming tree limbs**
- **Chimney cleaning**
- **Storm clean-up/repair**
- **Re-roofing/Re-shingle**



Single D Application

**Limitless Possibilities. Ask the Expert.**

Technical Service: 800.873.5242  
[www.millerfallprotection.com](http://www.millerfallprotection.com)

**Honeywell Industrial Safety**

900 Douglas Pike  
Smithfield, RI 02917

**USA**

Phone: 800.430.5490  
Fax: 800.322.1330

**Canada**

Phone: 888.212.7233  
Fax: 888.667.8477

**⚠** This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.