










Product Family  
**North Anchorage Connectors**



**Product Numbers & Ordering Information**

	Product Numbers	Details
	FP3730	<b>Anti Rollout Anchorage D</b> 1/2" Bolt on D-ring
	FP83	<b>Karabiner - Pear Shaped</b> Autolocking Carabiner, large pear shaped, steel, 2-1/4" (57mm) opening.
	FP86	<b>Karabiner</b> Autolocking Carabiner, steel, 19 mm (3/4") opening.
	FP86B	<b>Karabiner With Captive pin</b> Autolocking Carabiner, steel, 19 mm (3/4") opening, with captive pin.
	FP87	<b>Karabiner - Aluminum</b> Autolocking Carabiner, aluminum, 19 mm (3/4") opening, with captive pin.
	FP88	<b>Karabiner</b> Autolocking carabiner, large, steel offset D, 25 mm (1") opening.
	FP89	<b>Karabiner - Aluminum Pear Shape</b> Autolocking carabiner, large, steel offset D, 25 mm (1") opening.



FP90B

**Temporary Roof Anchor**  
Disposable steel roof anchor



FP92/2HQ

**Bent Wire Scaffold Hook**  
3-1/2" gate opening; Steel

---

**Additional Information**

1-888-212-SAFE (7233)

## Overview

### Key Features

North Anchorage connectors are high strength and can be used almost anywhere an anchorage point is needed.

### Recommended Industries/Use

- Construction
- Manufacturing
- Utilities

### Hazards

- Fall from height

### Regulations

- Regulations - ANSI Z359.1
- Regulations - OSHA

## Specifications

### Minimum Breaking Strength

- 5,000 lbs (22.2 kN)

## Training & Proper Use

See Operating and Maintenance Instruction Manual for details.

## Technical Support

1.800.873.5242 or [hsptechnfocon@honeywell.com](mailto:hsptechnfocon@honeywell.com)