










Product Family North Anchorage Connectors



Product Numbers & Ordering Information

	Product Numbers	Details
	FP3730	Anti Rollout Anchorage D 1/2" Bolt on D-ring
	FP83	Karabiner - Pear Shaped Autolocking Carabiner, large pear shaped, steel, 2-1/4" (57mm) opening.
	FP86	Karabiner Autolocking Carabiner, steel, 19 mm (3/4") opening.
	FP86B	Karabiner With Captive pin Autolocking Carabiner, steel, 19 mm (3/4") opening, with captive pin.
	FP87	Karabiner - Aluminum Autolocking Carabiner, aluminum, 19 mm (3/4") opening, with captive pin.
	FP88	Karabiner Autolocking carabiner, large, steel offset D, 25 mm (1") opening.
	FP89	Karabiner - Aluminum Pear Shape Autolocking carabiner, large, steel offset D, 25 mm (1") opening.



FP90B

Temporary Roof Anchor
Disposable steel roof anchor



FP92/2HQ

Bent Wire Scaffold Hook
3-1/2" gate opening; Steel

Additional Information

1-888-212-SAFE (7233)

Overview

Key Features

North Anchorage connectors are high strength and can be used almost anywhere an anchorage point is needed.

Recommended Industries/Use

- Construction
- Manufacturing
- Utilities

Hazards

- Fall from height

Regulations

- Regulations - ANSI Z359.1
- Regulations - OSHA

Specifications

Minimum Breaking Strength

- 5,000 lbs (22.2 kN)

Training & Proper Use

See Operating and Maintenance Instruction Manual for details.

Technical Support

1.800.873.5242 or hspotechinfo@honeywell.com