

SF™ SuperFit Premium Overboot

SF Chem Overboot: Made in the USA, has been tested to the chemical requirements of the Millitary Spec MIL-O-43995C and the CID A-A-59520. This boot features a highly durable injection molded construction with tabbed grips and elastic loops. The construction is a one-piece molded overshoe to eliminate possible leaks in reinforced areas. This boot also features a slip-coated interior and a slip-resistant, self-cleaning outsole.

Honeywell

Product Numbers & Ordering Information

Product Numbers	Details
11095	Servus®, SF Overboot, PVC Overboot – SF Chem – PVC – 12 in (30.5 cm) – Black - Men's sizes: Small to Extra-Large

Packaging Information

1 pair per bag, 12 or 6 per case

Hazardous Materials

NA

Overview

Key Features

Over-sized design to fit over leather work boots protecting them from harsh environments, increasing the longevity of
expensive footwear • PVC injection molded footwear is 100% waterproof protection to keep leather work boots and feet
dry • Extra large molded kick-off lugs for easy boot removal • Boot buttons are molded to eliminate seams, providing
waterproof protection • Closure loops are tabbed to allow for easy, one hand closure, even when wearing gloves

Recommended Industries/Use

• Agriculture • Construction • Law Enforcement • Utilities

Hazards

• Slip • Splash

Regulations

- American Society of Testing and Materials ASTM F2413-11
- ANSI Z41-1991 OSHA 1910.136 states; The employer shall ensure that each affected employee uses protective
 footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects, or objects

SF™ SuperFit Premium Overboot

piercing the sole, and where such employee's feet are exposed to electrical hazards. For more information go to www.osha.gov.

• Canadian Standards Association - CAN/CSA Z195-09

Historical Brand

Norcross Safety Products

Warranty Information

Each new Product manufactured and/or sold by NSP is warranted to be free from defects in material and/or workmanship. NSP's responsibility is limited to, at its option repairing or replacing any instrument or part thereof, or issuing a credit, for a period of one year after shipment. NSP's warranty sets forth the limit of NSP's responsibility. ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS, ARE EXCLUDED

Specifications

Construction

Injection molded

Height

• Range 4 inch (10.2 cm) to 12 inch (30.5 cm)

Insole

None

Insulated

No

Material

PVC

Metatarsal Protection

None

Sizes

• Men's sizes XS - XL

Steel Midsole Protection

None

Steel Toe Protection

None

Tread

• Extra wide grip outsole

Waterproof

Yes

Technical Support

Technical Support is available Monday through Friday, 8:00 AM to 7:00 PM EST. 1.800.873.5242 hsptechsupport@honeywell.com

© Honeywell International Inc.