

Model: CLASSIC pure standard M

Reference no.: 29-200660-006

Correct use: clean rooms - passive storage



Product group:	safety storage cabinet
Fire resistance (FR):	Type 90
Catalogue page:	351
Doors can be opened with minimum effort, design:	wing door
Door technology:	classical
Door hinge:	right
In case of fire, automatic and blockage-free self-closing via thermocouple:	yes
Access control with cylinder lock:	✓
Enhanced ventilation concept - ventilation in every cabinet level:	✓
Visual inspection of ventilation cut-off flaps:	✓

Outer width [mm]:	595 - (23.43 inch)
Outer depth [mm]:	595 - (23.43 inch)
Outer height [mm]:	2080 - (81.89 inch)
Base height [mm]:	85
Easy transportation due to accessible base:	✓
Adjustable feet for level equalisation:	✓
Base version:	ToeKick
Material outer carcass:	sheet steel, powder-coated
Gross weight [kg]:	286 - (630.52 lbs)
Inner width [mm]:	499 - (19.65 inch)
Inner depth [mm]:	446 - (17.56 inch)
Inner height [mm]:	1830 - (72.05 inch)
Material inner carcass:	sheet steel, powder-coated
Maximum volume of the largest individual container [l]:	19 - (5.02 gal)
Collection volume [l]:	21 - (5.55 gal)
Bottom tray interior:	bottom tray
Number of bottom trays:	1
Perforated sheet interior:	perforated sheet insert
Number of perforated sheet inserts:	1
Earthing connection according to TRGS 727 available:	1
Number of earthing connections:	2

Exhaust air connection included:	NW 75/110
Standing surface material:	stainless steel
Load-bearing capacity per standing surface with uniformly distributed load [kg]:	75 - (165.35 lbs)
Adjustment height 1 left [mm]:	398 - (15.67 inch)
Adjustment height 2 left [mm]:	398 - (15.67 inch)
Adjustment height 3 [mm]:	398 - (15.67 inch)
Adjustment height 4 left [inch]:	392 - (15.43 inch)
Mark of approval by TÜV:	GS mark
Type-tested by recognised test institutes according to:	DIN EN 14470-1
TÜV-tested according to:	DIN EN 14470-1, EK5/AK4 09-10
Further TÜV testing (1):	DIN EN 14727
Further TÜV testing (2):	TRGS 510 Annex 3
Added value mark of approval by TÜV:	High Quality
Declaration of conformity:	CE