

Straight-Sided Open-Head UN Rated Poly Drum

DRM1060 30 gal., UN1H2/Y180/S, .125" Thick

Straight sidewall, UN Rated open top drum has ribs for extra stength and allows broader use of drum grabs and other equipment.

- Straight sidewalls allow broader use of drum grabs, parrot beak lifters and other equipment that can't move tapered drums
- Ribs add strength and rigidity; UN Rated for storage and transport of solid hazardous materials
- High-density polyethylene won't rust or corrode
- Quick-release lever lock band can be wire sealed to deter unauthorized access
- Compatible with a wide range of liquids and chemicals

Specifications

Specifications	
Lining	Unlined
Thickness	.125" Thick
Color	Blue
Dimensions	ext. dia. 18.5" x 29.4" H
Storage Capacity	30 gal.
Bung Type	No Bung Holes
Drum Type	Poly Drum
Interior Dimensions	17.5" Dia. x 29" H
Lid Type	Open-Head - Quick-Style Lever Lock Band
Temperature Limit	160°F (71°C) Maximum Temperature
Sold as	1 each
Weight	15.5 lbs.
# per Pallet	3
Composition	Polyethylene (HDPE)
UNSPSC	24112109
Pigalog® Page Number	Page 311
Metric Equivalent	
mouro =quivaioni	

113.6 L

7 kg

Technical Information

Storage Capacity

Weight

Certifications, Approvals and Ratings

UN1H2/Y180/S



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com