




Non-Skid Step Tape

FLM640 2" x 60', 1 roll

Durable epoxy-coated grit helps create safe footing anywhere.

- Durable mineral grit compound creates a non-skid surface for safe footing throughout your facility
- Grit is sealed with 2-part epoxy resin for durability and to prevent shedding
- Resists oil, water and heavy foot traffic for long service life
- Adhesive features low initial tack for minutes of easy repositioning
- Tape removes without residue
- Just cut to length, remove protective backing and apply



Item#	Description	Dimensions	Weight
FLM640-SY	Safety Yellow,	2" W x 60' L	1.705 lbs.
FLM640-HZ	Black/Yellow Hazard Stripe,	2" W x 60' L	1.705 lbs.
FLM640-BK	Black,	2" W x 60' L	1.705 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM640-SY	Safety Yellow,	5.1cm W x 18m L	.8 kg
FLM640-HZ	Black/Yellow Hazard Stripe,	5.1cm W x 18m L	.8 kg
FLM640-BK	Black,	5.1cm W x 18m L	.8 kg

Specifications

Thickness	30 mil Black, 25 mil Hazard & Yellow
Dimensions	2" W x 60' L
Installation Method	Self-Adhesive
Sold as	1 roll
Weight	1.705 lbs.
Composition	Mineral-Abrasive Compound

Metric Equivalent

Dimensions	5.1cm W x 18m L
------------	-----------------

Weight	.8 kg
--------	-------

Technical Information

Certifications, Approvals and Ratings

NFSI Certified

Technical Documents

29 CFR 1910.24(f)

29 CFR 1910.26(a)(1)(v)



One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com