



Non-Skid Step Tape

FLM642 6" x 60', 1 roll

Durable epoxy-coated grit helps create safe footing anywhere.

- Durable mineral grit compound creates a non-skid surface for safe footing throughout your facility
- Grit is sealed with 2-part epoxy resin for durability and to prevent shedding
- Resists oil, water and heavy foot traffic for long service life
- Adhesive features low initial tack for minutes of easy repositioning
- Tape removes without residue
- Just cut to length, remove protective backing and apply



| Item# | Description | Dimensions | Weight |
|-----------|-----------------------------|--------------|------------|
| FLM642-SY | Safety Yellow, | 6" W x 60' L | 5.418 lbs. |
| FLM642-HZ | Black/Yellow Hazard Stripe, | 6" W x 60' L | 5.418 lbs. |
| FLM642-BK | Black, | 6" W x 60' L | 5.418 lbs. |

Metric Equivalent:

| Item# | Description | Dimensions | Weight |
|-----------|-----------------------------|------------------|--------|
| FLM642-SY | Safety Yellow, | 15.2cm W x 18m L | 2.5 kg |
| FLM642-HZ | Black/Yellow Hazard Stripe, | 15.2cm W x 18m L | 2.5 kg |
| FLM642-BK | Black, | 15.2cm W x 18m L | 2.5 kg |

Specifications

| | |
|---------------------|--------------------------------------|
| Thickness | 30 mil Black, 25 mil Hazard & Yellow |
| Dimensions | 6" W x 60' L |
| Installation Method | Self-Adhesive |
| Sold as | 1 roll |
| Weight | 5.418 lbs. |
| Composition | Mineral-Abrasive Compound |

Metric Equivalent

| | |
|------------|------------------|
| Dimensions | 15.2cm W x 18m L |
|------------|------------------|

| | |
|--------|--------|
| Weight | 2.5 kg |
|--------|--------|

Technical Information

Certifications, Approvals and Ratings

NFSI Certified

Technical Documents

29 CFR 1910.24(f)

29 CFR 1910.26(a)(1)(v)



One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com