

PIG® Stat-Mat® Absorbent Pad

MAT215 Lightweight, 15" x 20", 200 pads

Clean up spilled fuels and solvents with the only pads proven to dissipate static.



- The best mat you can buy to reduce the risk of electrostatic discharge; a critical precaution around flammable liquids and vapors
- Stat-Mat Pads and Rolls pass NFPA 99 standards for static decay and surface resistivity, making them perfect for fueling areas and solvent cleanup
- Absorbs and retains oils and fuels - including acetone, benzene, gasoline, toluene, xylene, mineral spirits and jet fuels - but not water
- Lasts 2X longer than ordinary mats for fewer change-outs; Eight layers of 100% polypropylene are thermally bonded to make PIG Mat the strongest mat on the market; won't rip, tear or fray even when saturated
- Exclusive dimple pattern speeds wicking of liquid throughout mat for faster, easier cleanup
- Highly absorbent, fine-fiber construction won't leave behind liquids or fiber residue
- Packaged in special static-dissipative bags to help reduce static charge buildup
- Floats to clean up spills on water
- Flame-resistant material won't burn immediately like cellulose mats; melts when exposed to high heat while on the job
- White color tells you it's only for oils and fuels
- Pads are ideal for catching drips and soaking up spills
- Easy-tear perforations let you take only what you need, so you use less mat and save money
- Light-weight construction is economical for small tasks and cleanups



Specifications

Static-Dissipative	Yes
Floating	Yes
Reusable	No
Wringable	No
Fluid Absorbed	Oils, Fuels, Other Oil-Based Liquids Only

Color	White
Dimensions	15" W x 20" L
Mat Weight	Lightweight
Absorbency	Up to 22 gal. per bag
Absorbency per	Up to 14.08 oz. per pad
Brand	PIG
Perforated	Yes
Sold as	200 pads per bag
Weight	17 lbs.
# per Pallet	30
Composition	Polypropylene
UNSPSC	47131901
UV Resistant	No
Pigalog® Page Number	Page 53

Metric Equivalent

Absorbency per	Up to 416.3 mL per pad
Absorbency	Up to 83.3 L per bag
Dimensions	38.1cm W x 50.8cm L
Weight	7.7 kg

Technical Information

Certifications, Approvals and Ratings

NFPA 99,NFPA 77

Technical Documents

PIG® Oil-Only Absorbents

29 CFR 1910.106(h)(7(i)(a)

29 CFR 1910.22(a)(2)

40 CFR 112.7

40 CFR 122.26



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com

