



PIG® Grippy® Adhesive-Backed Absorbent Mat

MAT3224 Mediumweight, 36" x 50', 1 roll

Make the switch to the mat that sticks! Our most durable absorbent runner is the only one that stays put no matter what® - even under forklift traffic.

- Full-coverage Grippy® adhesive backing holds tight but peels up easily
- No bunching, rippling, flipping or shifting; lays flat and stays flat to help eliminate trips, slips and falls
- Sticks to most commercial floor surfaces including concrete, VCT, linoleum, ceramic tile, quarry tile and laminate flooring
- Heat-fused and needle-punched for incredible durability; won't rip, shred or fray under constant walk-on or wheeled traffic, even from forklifts
- Tested and Certified by the National Floor Safety Institute (NFSI) - When used as part of your floor safety program, high-traction walking surfaces such as PIG Grippy Mat have been proven to reduce slip-and-fall claims by as much as 90%
- 100% polypropylene fibers absorb and retain water, oils, grease, coolants and solvents; prevents dirt, sand and liquids from being tracked onto clean floors
- Liquidproof barrier layer prevents seepage to keep floors completely dry
- Dark color hides grime so mat stays down longer
- Ideal for high-traffic areas like walkways, hallways, entrances and exits
- Easily cuts to size with scissors or utility knife; apply to any clean, dry, oil-free surface



ltem#	Description	Dimensions	Weight	
MAT3224-BK	Black,	36" W x 50' L	12.6 lbs.	
Metric Equivalent:				
ltem#	Description	Dimensions	Weight	
MAT3224-BK	Black,	91.4cm W x 15m L	5.7 kg	

Specifications

Antimicrobial	No		
Backing Material	Adhesive-Backed		
Indoor/Outdoor	Indoor		
Traffic Level	Heavy Foot Traffic; Drive-Over		
Fluid Absorbed	Oils, Coolants, Solvents, Water – Universal		
Dimensions	36" W x 50' L		
Mat Weight	Mediumweight		
Absorbency	Up to 5.75 gal. per roll		
Brand	PIG		
Core Diameter	3"		
Industry	Industrial Facilities; Shops & Garages		
Perforated	No		
Poly-Backed Barrier	Yes		
Storage Temp Range	Store between 32°F and 120°F		
Temperature Limit	Surface temps from 55°F to 120°F		
Walking Surface	Absorbent Top		
Sold as	1 roll		
Weight	12.6 lbs.		
New Pig Patent	Pending		
# per Pallet	28		
Composition	Absorbent - Polypropylene Adhesive Backing - Proprietary Adhesive Material		
UNSPSC	47131901		
UV Resistant	No		
Metric Equivalent			
Absorbency	Up to 21.8 L per roll		
Dimensions	91.4cm W x 15m L		
Weight	5.7 kg		
Technical Information			
Certifications, Approvals and Ratings			
NFSI Certified, ANSI B101.1- 2009			
Technical Documents			
PIG Grippy Mat			

PIG® GRIPPY® ABSORBENT MAT PRODUCT DISCLAIMER & WARRANTY INFORMATION

Case Study - General Cable

29 CFR 1910.22(a)(2)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com