


PIG® Grippy® Adhesive-Backed Absorbent Mat for Garage Floors

MAT3251 Mediumweight, 32" x 40", 1 roll

Make the switch to the mat that sticks! Absorbent runner catches drips from vehicles or industrial equipment, and it won't blow away when the door is open.

- Adhesive-backed absorbent mat stays exactly where you put it with no shifting or bunching up underfoot
- Fits perfectly underneath vehicles to protect shop floors from oily leaks and drips; reduces cleanup time to keep your shop productive
- Sticks to most commercial floor surfaces including concrete, VCT, linoleum, ceramic tile, quarry tile and laminate flooring
- Proprietary adhesive sticks to the floor with a super-tight grip, but can be easily removed and repositioned so you can reuse the mat until it becomes saturated
- Tough, spunbond top layer with heavy-duty zigzag stitching stands up to rolling tires and service bay foot traffic
- Eight layers of fine-fiber polypropylene safely absorb and retains oils, coolants, water, grease, gasoline, solvents, auto fluids, paint overspray, battery acid and most other liquids
- Leakproof backing prevents absorbed liquid from soaking through to the floor
- Dark color hides grime so the mat looks cleaner longer
- Mat ends are heat-cut for a finished, professional look
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Absorbent Mat have been proven to reduce slip-and-fall claims by as much as 90%



Specifications

Antimicrobial	No
Backing Material	Adhesive-Backed
Indoor/Outdoor	Indoor

Traffic Level	Heavy Foot Traffic; Drive-Over
Fluid Absorbed	Oils, Coolants, Solvents, Water – Universal
Color	Blue
Dimensions	32" W x 40" L
Mat Weight	Mediumweight
Recycled Content	25% or more Recycled Content
Absorbency	Up to .35 gal. per roll
Brand	PIG
Core Diameter	3"
Industry	Industrial Facilities; Shops & Garages
Perforated	No
Storage Temp Range	Store between 32°F and 120°F
Temperature Limit	Surface temps from 55°F to 120°F
Walking Surface	Absorbent Top
Sold as	1 roll
Weight	1.8 lbs.
New Pig Patent	Patent Pending
# per Pallet	500
Composition	Absorbent - Polypropylene Stitching - Polyester Adhesive Backing - Proprietary Adhesive Material
UNSPSC	47131901
UV Resistant	No
Pigalog® Page Number	Page 21

Metric Equivalent

Absorbency	Up to 1.3 L per roll
Dimensions	81.3cm W x 101.6cm L
Weight	.8 kg

Technical Information

Certifications, Approvals and Ratings

NFSI Certified,ANSI B101.1- 2009,Meets NFPA 99 Static Decay and Resistivity Requirements

Technical Documents

[PIG Grippy Mat](#)

[PIG® GRIPPY® ABSORBENT MAT PRODUCT DISCLAIMER & WARRANTY INFORMATION](#)

[Static Coefficient Of Friction \(SCOF\) Testing](#)

[Case Study - General Cable](#)

How to use PIG Grippy Absorbent Mat

White paper – Slip & Fall Prevention Secrets

PIG® Grippy® Absorbents

29 CFR 1910.22(a)(2)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com