











MAT504 Lightweight, 15" x 20", 200 pads

Lasts 2x longer than ordinary mats for fewer change-outs, while only absorbing oil and fuels, NOT water. Loves oil. Hates water. Brown color looks cleaner, longer.

- Brown color looks cleaner, longer, by blending in with most environments for both indoor and outdoor use; hides grime, so mat stays on the job longer
- Eight layers of 100% polypropylene are thermally bonded to make PIG Mat the strongest mat on the market; won't rip, tear or fray even when saturated
- Exclusive dimple pattern speeds wicking of liquid throughout mat for faster, easier cleanup
- Highly absorbent, fine-fiber construction won't leave behind liquids or fiber residue
- Absorbs oil and fuels, NOT water
- Floats to clean up spills on water
- Can be wrung out and incinerated after use to reduce waste or for fuels blending
- Flame-resistant material won't burn immediately like cellulose mats; melts when exposed to high heat while on the job
- Pads are ideal for catching drips and soaking up spills
- Easy-tear perforations let you take only what you need, so you use less mat and save money
- Light-weight construction is economical for small tasks and cleanups



Specifications

Mat Weight

| Static-Dissipative | No |
|--------------------|---|
| Floating | Yes |
| Reusable | No |
| Wringable | Yes |
| Fluid Absorbed | Oils, Fuels, Other Oil-Based Liquids Only |
| Color | Brown |
| Dimensions | 15" W x 20" L |

Lightweight

| Absorbency | Up to 22 gal. per bag |
|----------------------|-------------------------|
| Absorbency per | Up to 14.08 oz. per pad |
| Brand | PIG |
| Perforated | Yes |
| Sold as | 200 pads per bag |
| Weight | 17 lbs. |
| # per Pallet | 36 |
| Composition | Polypropylene |
| UNSPSC | 47131901 |
| UV Resistant | No |
| Pigalog® Page Number | Page 51 |

Metric Equivalent

| Absorbency per | Up to 416.3 mL per pad |
|----------------|------------------------|
| Absorbency | Up to 83.3 L per bag |
| Dimensions | 38.1cm W x 50.8cm L |
| Weight | 7.7 kg |

Technical Information

Technical Documents

Shrink Bale FAQ

PIG® Oil-Only Absorbents

29 CFR 1910.22(a)(2)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com