

PIG® Heavy-Duty 4-Drum Poly Spill Containment Pallet

PAK672 Holds (4) 55 gal. Plastic or Steel Drums, 62.5" x 62.5" x 8.75", 75 gal. Sump Capacity

The strongest pallets you can buy won't buckle or bow, even under the heaviest loads! Guaranteed for life.

- The strongest, most durable containment pallets you can buy won't buckle or bow. We guarantee it.
- Strong enough for long-term storage of liquids with high specific gravities
- Innovative design transfers weight to load-bearing channels to maximize capacity
- Molded-in sump catches leaks, drips and spills to help you comply with regulations and keep your storage areas clean and safe
- Low height means loading and unloading require less effort and drum tops are within easier reach
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals
- Textured grating adds traction and lifts out for easy sump access
- Optional drain plug lets you empty sump without removing drums or grating
- 4-way forklift entry allows easy movement from any direction (loaded or unloaded)
- Can also be used with IBC Containment Units
- We test all of our Containment Pallet designs at max load for months to ensure they can handle full capacity at your facility



Item#	Description	Dimensions	Weight
PAK672-BK-WOD	Black, Without Drain	62.5" W x 62.5" L x 8.75" H	140 lbs.
PAK672-BK-WD	Black, With Drain	62.5" W x 62.5" L x 8.75" H	140 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PAK672-BK-WOD	Black, Without Drain	158.8cm W x 158.8cm L x 22.2cm H	63.5 kg
PAK672-BK-WD	Black, With Drain	158.8cm W x 158.8cm L x 22.2cm H	63.5 kg

Specifications

Holds	(4) 55 gal. Plastic or Steel Drums
Dimensions	62.5" W x 62.5" L x 8.75" H
Recycled Content	48% Post-Industrial Recycled Polyethylene
Load Capacity UDL	9000 lbs.
Sump Capacity	75 gal.
Double-Stackable Unit	No
Drain	Optional Drain
Fork Truck Access	Four-Way Fork Access, Can Move Loaded
Grates	(2) 52" L x 26" W Grates
Use With Flammables	No
Sold as	1 each
Weight	140 lbs.
# per Pallet	10
Composition	Sump - LDPE w/ UV Inhibitor Grate - Polyethylene
UNSPSC	24101905
Pigalog® Page Number	<u>Page 369</u>

Metric Equivalent

Dimensions	158.8cm W x 158.8cm L x 22.2cm H
Load Capacity UDL	4082.4 kg
Sump Capacity	283.9 L
Weight	63.5 kg

Technical Information

Technical Documents

LDPE Products

[White paper – Should I be Worried about SPCC? 8 Things you need to know.](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

[40 CFR 264.175](#)

Disclaimers

Flammables Notice

If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.

