













Autoship Eligible

Specifications

Metric Equivalent

Absorbency per

Absorbency

Fluid Absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Color	White
Absorbency	Up to 8 gal. per box
Absorbency per	Up to 2 gal. per container
Unit Weight	2 lb.
Sold as	4 containers per box
Weight	11 lbs.
# per Pallet	54
Composition	Co-Polymer Proprietary Blend
Application	Solidifying
UNSPSC	47131902
Pigalog® Page Number	Page 69

Up to 7.6 L per container

Up to 30.3 L per box

PIG® Oil Solidifying Absorbent Powder

PLP500 Absorbs Oils, Fuels, Other Oil-Based Liquids Only, Absorbs up to 2 gal. per container, 4 containers

Solidifies absorbed oil and locks it into the material for easier cleanup.

- Permanently solidifies to "lock" in absorbed liquids; won't leak or revert to liquid state when handled or placed under pressure
- Allows easier, less expensive recovery and cleanup; may help you comply with EPA requirements when used to solidify waste prior to shipment or landfilling
- Environmentally friendly product absorbs oils and oil-based liquids, including fuels, solvents and paints (will not absorb water)
- High BTU value produces less than 0.1% ash content when burned; ideal for fuels blending and incineration
- Shaker bottle with handle makes it easy to apply absorbent directly onto the spill area

Weight 5 kg

Technical Information

Technical Documents

PIG® Oil Solidifying Absorbent Powder

29 CFR 1910.22(a)(2)

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com