

## **PIG® SpillBlocker® Dike**

PLR204 Ideal For Quick Spill Response, One 4" W x 10' L x 2.25" H Section

Confine and divert spills up to 2.25" deep with our original dike. Others look the same but only PIG delivers durable two-part construction.

- Exclusive New Pig formulation features a tear-resistant top layer and a flexible, tacky bottom layer that seals tight to smooth surfaces and blocks liquids
- Other dikes may look similar, but only PIG SpillBlocker Dikes have two-layer construction for superior performance
- 2.25" height is great for containing smaller spills
- Fast protection for when a spill is heading right for your drain; just place dike in front of spill to contain liquid
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- Polyurethane material resists water, oils and many chemicals
- Reusable dike cleans easily with soap and water



Item#	Description	Dimensions	Weight
PLR204-YW	Yellow,	4" W x 10' L x 2.25" H	30 lbs.
PLR204-BK	Black,	4" W x 10' L x 2.25" H	30 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
PLR204-YW	Yellow,	10.2cm W x 3m L x 5.7cm H	13.6 kg
PLR204-BK	Black,	10.2cm W x 3m L x 5.7cm H	13.6 kg

### Specifications

Traffic	Non-Weight Bearing
Barrier Dimensions	One 4" W x 10' L x 2.25" H Section
Dimensions	4" W x 10' L x 2.25" H
Ideal For	Quick Spill Response
Install/Deploy Type	Temporary/Removable Barrier
Intended Use	Smooth Surfaces

<b>Max liquid temp exposure</b>	Max Exposure Limit 225°F for up to 30 Minutes
<b>Storage Temp Range</b>	Store Between 0°F and 120°F
<b>Temperature Limit</b>	Works from 0°F to 160°F
<b>Sold as</b>	1 per box
<b>Weight</b>	30 lbs.
<b>New Pig Patent</b>	5,236,281
<b># per Pallet</b>	32
<b>Composition</b>	Polyurethane
<b>UNSPSC</b>	24101907
<b>Pigalog® Page Number</b>	<u><a href="#">Page 163</a></u>

## Metric Equivalent

<b>Dimensions</b>	10.2cm W x 3m L x 5.7cm H
<b>Weight</b>	13.6 kg

## Technical Information

### Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[PIG Spillblocker Dike Instructions](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

### Disclaimers

#### [Urethane Notice](#)

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)