


PIG™ Conical Drain Plug

PLR209 Fits 3" Dia. Drains

Seal drains below the grate without the hassle or permanence of cement.

- Durable polyurethane plug forms a liquid-tight, chemical-resistant seal in seconds
- Just wedge plug in drain for an easy alternative to permanently sealing your drains with cement
- Installed plug is low-profile enough to fit below floor grate
- Allows your drain to function normally when plug is not in place; removes easily with hand-tools



Specifications

| | |
|----------------------|---|
| Color | Yellow |
| Dimensions | 5.25" W x 3.35" L x 5" H |
| Drain Size | 3" Dia. Drains |
| Ideal For | Long-Term Use |
| Sold as | 1 each |
| Weight | 1.5 lbs. |
| # per Pallet | 2000 |
| Composition | Plug - Polyurethane Eye Bolt - Metal |
| UNSPSC | 40141738 |
| UV Resistant | No |
| Pigalog® Page Number | Page 173 |

Metric Equivalent

| | |
|------------|-------------------------------|
| Dimensions | 13.3cm W x 8.5cm L x 12.7cm H |
| Weight | .7 kg |

Technical Information

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers

[Urethane Notice](#)

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com