



PIG® SpillBlocker® Dike

PLR212 Ideal For Small Leaks, One 2.25" W x 10' L x 1.375" H Section

Don't waste a big blocker on a small leak. This 1.375"H SpillBlocker is just right for leaky machinery until you can make repairs.

- Fast protection for when a leak is starting to spread; just surround machine with dike to contain liquid
- Exclusive New Pig formulation is flexible and tacky; seals tight to smooth surfaces and blocks liquids
- Built-in, interlocking end joints create a liquid-proof seal and allow you to join as many sections as you need without extra parts
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- Polyurethane material resists water, oils and many chemicals
- High-visibility yellow color draws attention to spill for increased safety
- Reusable dike cleans easily with soap and water



Specifications

Traffic	Non-Weight Bearing
Barrier Dimensions	One 2.25" W x 10' L x 1.375" H Section
Color	Yellow
Dimensions	2.25" W x 10' L x 1.375" H
Barrier Type	Urethane Blocker
Ideal For	Small Leaks
Install/Deploy Type	Temporary/Removable Barrier
Intended Use	Smooth Surfaces
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes
Storage Temp Range	Store Between 0°F and 120°F
Temperature Limit	Works from 0°F to 160°F up to 1 Year
Sold as	1 per box
Weight	10.4 lbs.
New Pig Patent	5,236,281

NSN (National Stock Number)	7930-01-436-8320
# per Pallet	72
Composition	Polyurethane
UNSPSC	24101907
Pigalog® Page Number	<u>Page 175</u>

Metric Equivalent

Dimensions	5.7cm W x 3m L x 3.5cm H
Weight	4.7 kg

Technical Information

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[PIG Spillblocker Dike Instructions](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com