

PIG® Water-Filled Containment Dike

PLR225 Ideal For Washdowns, Temporary Water Diversion, 4.5" W x 10' L x 2" H When Filled, 1 each

Keep washdown liquids in check with our economical water-filled containment dike. Rolls up for easy storage when you're done.

- Heavy-duty dike is durable, reusable and moldable; just place on ground and fill with water to create a gravity-based berm (not 100% watertight)
- Ideal for controlling and directing water from pressure washing operations (not for long-term containment of liquids)
- High-visibility orange dike helps prevent trips and falls during washdowns
- Convenient valve for quick filling and emptying

Specifications

Traffic	Non-Weight Bearing
Dimensions When Filled	4.5" W x 10' L x 2" H When Filled
Height When Filled	2" When Filled
Capacity	9 gal. per Barrier
Color	Orange
Dimensions	4.5" W x 10' L x 2" H
Ideal For	Washdowns, Temporary Water Diversion
Install/Deploy Type	Temporary/Removable Barrier
Temperature Limit	Works from -20°F to 150°F
Sold as	1 each
Weight	1.166 lbs.
Composition	Boom - 18 oz. Vinyl w/ Polyester Yarn Reinforcement Reinforced Ends - Steel
UNSPSC	24101907
Pigalog® Page Number	Page 167

Metric Equivalent

Dimensions 11.4cm W x 3m L x 5.1cm H

Weight .5 kg

Technical Information

Technical Documents

PIG Water-Filled Containment Boom

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com