

PIG® High-Volume SpillBlocker® Dike

PLR254 Ideal For Quick Spill Response, One 4.5" W x 5' L x 6.75" H Section

Our tallest SpillBlocker dikes are designed to handle high-volume spills and pooling liquids.

- Exclusive New Pig formulation features a tear-resistant top layer and a flexible, tacky bottom layer that seals tight to smooth surfaces and blocks liquids
- Taller height is great for containing deeper pools of liquid and larger flows
- Built-in dovetail connectors create a liquid-proof seal and allow you to join as many sections as you need without extra parts
- Fast protection for when a large spill is heading right for your drain
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- High-visibility lime-green top color draws attention to spill for increased safety
- Polyurethane material resists water, oils and many chemicals
- Smaller sections are easy to handle and deploy
- Reusable dike cleans easily with soap and water



Item#	Description	Dimensions	Weight
PLR254-NG	Hi-Viz Green,	4.5" W x 5' L x 6.75" H	30.5 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PLR254-NG	Hi-Viz Green,	11.4cm W x 152.4cm L x 17.1cm H	13.8 kg

Specifications

Traffic	Non-Weight Bearing
Barrier Dimensions	One 4.5" W x 5' L x 6.75" H Section
Dimensions	4.5" W x 5' L x 6.75" H
Barrier Type	Urethane Blocker
Ideal For	Quick Spill Response
Install/Deploy Type	Temporary/Removable Barrier

Intended Use	Smooth Surfaces
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes
Storage Temp Range	Store Between 0°F and 120°F
Temperature Limit	Works from 0°F to 160°F up to 1 Year
Sold as	1 per box
Weight	30.5 lbs.
New Pig Patent	5,236,281
# per Pallet	36
Composition	Polyurethane
UNSPSC	24101907
Pigalog® Page Number	<u>Page 175</u>

Metric Equivalent

Dimensions	11.4cm W x 152.4cm L x 17.1cm H
Weight	13.8 kg

Technical Information

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com