

## **PIG® SpillBlocker® Dike**

PLR267 Ideal For Quick Spill Response, Two 3.5" W x 5' L x 3" H Sections

Quickly deploy these easy-to-handle spill dikes to contain liquids up to 3" deep. Built-in connectors let you join multiple sections.

- Exclusive New Pig formulation features a tear-resistant top layer and a flexible, tacky bottom layer that seals tight to smooth surfaces and blocks liquids
- Fast protection for when a spill is heading right for your drain; just place dike in front of spill to contain liquid
- Built-in dovetail connectors create a liquid-proof seal and allow you to join as many sections as you need without extra parts
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- 3" height is great for containing deeper pools of liquid and larger flows
- Polyurethane material resists water, oil and many chemicals
- Two smaller 5' sections are easy to handle and deploy
- Reusable dikes clean easily with soap and water



Item#	Description	Dimensions	Weight
PLR267-YW	Yellow,	3.5" W x 5' L x 3" H	25 lbs.
PLR267-BK	Black,	3.5" W x 5' L x 3" H	25 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
PLR267-YW	Yellow,	8.9cm W x 152.4cm L x 7.6cm H	11.3 kg
PLR267-BK	Black,	8.9cm W x 152.4cm L x 7.6cm H	11.3 kg

### Specifications

Traffic	Non-Weight Bearing
Barrier Dimensions	Two 3.5" W x 5' L x 3" H Sections
Dimensions	3.5" W x 5' L x 3" H

<b>Barrier Type</b>	Urethane Blocker
<b>Ideal For</b>	Quick Spill Response
<b>Install/Deploy Type</b>	Temporary/Removable Barrier
<b>Intended Use</b>	Smooth Surfaces
<b>Max liquid temp exposure</b>	Max Exposure Limit 225°F for up to 30 Minutes
<b>Storage Temp Range</b>	Store Between 0°F and 120°F
<b>Temperature Limit</b>	Works from 0°F to 160°F up to 1 Year
<b>Sold as</b>	2 per box
<b>Weight</b>	25 lbs.
<b>New Pig Patent</b>	5,236,281
<b># per Pallet</b>	60
<b>Composition</b>	Polyurethane
<b>UNSPSC</b>	24101907
<b>Pigalog® Page Number</b>	<u><a href="#">Page 175</a></u>

## Metric Equivalent

<b>Dimensions</b>	8.9cm W x 152.4cm L x 7.6cm H
<b>Weight</b>	11.3 kg

## Technical Information

### Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[White paper – Should I be Worried about SPCC? 8 Things you need to know.](#)

[PIG® Blocker Family](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

### Disclaimers

#### Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.

