

## **PIG™ Pipe Wrap Repair Kit for Lines & Joints Under Pressure**

PTY124 Pressurized, For 2.5" - 4" dia.

Fast, easy way to permanently fix broken, corroded or leaking pipes to beyond their original strength.

- Each kit contains materials for restoring one pipe or joint, even if pressurized up to 60psi
- Works on most pipes, including PVC, copper, galvanized steel, rubber, lead, iron and stainless steel
- Materials adhere to wet or dry surfaces to allow repairs without draining pipes
- Pressure-sensitive tape and PIG® Repair Putty apply underneath outer wrap to strengthen seal
- Polyurethane-impregnated fiberglass wrap exceeds original bursting pressure rating of pipes
- Nitrile gloves protect hands during repair
- Cures in approximately 30 minutes at 75°F
- Final repair is not affected by salt water
- NSF Certified for safe use on potable water lines



### Specifications

Cure Time	30 Minutes at 75°F (24°C)
Pipe Size	2.5" - 4" dia.
Pipe Pressure	Pressurized
Temperature Limit	300°F (149°C) Continuous/500°F (260°C) Intermittent
Sold as	3 per box
Weight	3.76 lbs.
# per Pallet	432
Composition	Putty - Epoxy Pressure-Sensitive Tape - Rubber Gloves - Nitrile Wrap - Polyurethane/Fiberglass
Includes	3 - 2.5" L Putty Sticks 1 - 9' L x 1" W Pressure-sensitive Tape 1 - Pair Nitrile Gloves 1 - 15' L x 4" W Polyurethane-impregnated Fiberglass Wrap
Shelf Life	2 years
UNSPSC	31201519

## Metric Equivalent

Weight	1.7 kg
--------	--------

## Technical Information

### Certifications, Approvals and Ratings

NSF Certified

#### CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Japan.

### Certifications, Approvals and Ratings

NSF Certified

#### CountryNoShip

This product is subject to export restrictions and cannot be shipped to: Canada, European Union, Japan.

## Technical Documents

[Instructions for Using PIG® Pipe Wrap Repair Kit on Pipes Under Pressure](#)

[PIG® Multi-Purpose Repair Putty](#)

[PIG® Wrap for Pipes](#)



# New Pig

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)