





PIG™ Plug-N-Seal® Patching Paste

PTY220 For Fuel Tanks, Steel Drums & Containers, 1 - 1 lb. Container

Even in cold temperatures, our ready-to-use paste instantly stops leaks for up to 2 hours.

- Temporarily stops leaks even in cold temperatures - until system can be drained or leak source contained
- Excellent chemical resistance makes it ideal for flammable or hazardous leaks
- No preparation needed, even on dirty or rusty surfaces
- Temporarily stops leaks from 2 minutes up to 2 hours
- Ready to use without mixing



Specifications

Use With	Fuel Tanks, Steel Drums & Containers
Color	Gray
Dimensions	ext. dia. 3.5" x 2.75" H
Repair Type	Temporary
Temperature Limit	32°F (0°C) to 150°F (66°C)
Sold as	1 each
Weight	1 lb.
# per Pallet	600
Composition	Bentonite Clay & Water w/ Polymer Base
Shelf Life	2 years
UNSPSC	47131903
Volume	1 lb. Container
Pigalog® Page Number	Page 271

Metric Equivalent

Dimensions ext. dia. 8.9cm x 7cm H

Weight .5 kg

Technical Information

Technical Documents

PIG® PLUG-N-SEAL® Patching Paste



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com