





PIG® Pipe Leak Diverter

TLS200 Pipes, Diverter Only, 12" x 12"

Purpose-built design catches pipe leaks or condensation to protect equipment, inventory and personnel.

- Hangs from a leaking pipe to catch nuisance leaks and channel them to a floor drain or collection container
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Built-in grommets and included 14"-long rubber straps make it easy to hang from an overhead pipe
- Choose yellow for high visibility, gray to blend with plant ceilings or clear to monitor leaks
- Flow rate of 3.33 gallons per minute when used with a 1/2" ID hose
- Need a custom size or solution? Just call 1-800-HOT-HOGS (468-4647)



Item#	Description	Dimensions	Weight
TLS200-YW	Yellow,	ext. dia. 12" x 12" H	2 lbs.
TLS200-GY	Gray,	ext. dia. 12" x 12" H	2 lbs.
TLS200-CL	Clear,	ext. dia. 12" x 12" H	2 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS200-YW	Yellow,	ext. dia. 30.5cm x 30.5cm H	.9 kg
TLS200-GY	Gray,	ext. dia. 30.5cm x 30.5cm H	.9 kg
TLS200-CL	Clear,	ext. dia. 30.5cm x 30.5cm H	.9 kg

Specifications

Style	Diverter Only
Dimensions	ext. dia. 12" x 12" H
Drainage Hose Included	No

Hanging Straps Included	Yes
Hose Connector	.75"
Installation Method	Hanging Straps
Shape	Circle
Sold as	1 each
Weight	2 lbs.
# per Pallet	288
Composition	Diverter (Colors) - PVC, Polyester Diverter (Clear) - PVC w/ Polyester Reinforcement
	Straps - Rubber
Application	
Application Flow Rate	Straps - Rubber
	Straps - Rubber Pipes

Metric Equivalent

Dimensions	ext. dia. 30.5cm x 30.5cm H
Weight	.9 kg

Technical Information

Technical Documents

Instructions for Assembling PIG® Leak Diverter System

Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com